



Family

**Catalog Number:** BVNZ-P488S  
**Product ID:** 7TAA292150R0336  
**UPC Number:** 78620995292  
**EAN Number:** 07630030230417  
**Status:** Active

VNZ Straight Connector with Strain Relief, PG Thread for IP68 Static Conduit - Thread PG 48, Fits to Conduit Size NW/Metric 48/50, Color Black

### North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	PMA
Type	Connectors-Strain Relief
Application	For Use In Machine and Plant Construction
Size	NW48
Material	Polyamide 6
Insulation Class	IP68
Color	Black
Connection	PG48
Temperature Rating	-40 Degrees C to 105 Degrees C; Short Term to 160 Degrees C

### European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	50mm
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Other
Thread connection size	PG48
Thread material	Polyamide
Thread length	14mm
Total length	112mm
Material	Polyamide
Material sealing	No sealing
Colour	Black
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UR	Y
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-40 - +105°C

### Packaging

Inner Quantity	10
Outer Quantity	50
Outer Dimensions (inches)	15.748x11.811x8.661
Weight Uom	0.31 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)