



## Flexible Conduits & Fittings

### T&B Catalog Number:

BVWV-M120

### UPC Number:

78620995382

### Status:

Active

### Description:

PMAFIX 90 degree black one-piece universal elbow , material - polyamide 6, conduit size NW - 10, thread size - M12 x 1.5.

### Application

In a wide range of applications where it is important that the cable protection system offers a high grade of sealing and safety.

### Characteristics

High pull-out strength values

Easy installation with the oval clip guarantees an excellent connection to PMAFLEX conduits.

IP rating of up to IP68 can be achieved with the corresponding seals, NVN3 + SVN4.

Self-extinguishing, free of halogen and cadmium and are extremely shock resistant

Fits both conduit profiles - Fine (T) and coarse (G)

### General

Material	Polyamide 6
Color	Black
Thread Type	Metric
Compatible With	PMAFLEX

### Dimension Information

Fits to Conduit Size (NW)	10
Fits to Conduit Size (metric)	12
Fits to Conduit Size (inches)	5/16
Thread Size (Metric)	M12 x 1.5

### Technical Information

Temperature Range-Continuous (Celsius)	-40 degree C to +105 degree C
Temperature-Short-Term (Celsius)	+160 degree C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website

### Specifications

3dmodel	Available on Website
---------	----------------------

### IP Ratings

IP Rating	IP68 stat. / IP67 dyn.
-----------	------------------------

### Packaging

T&B Inner Pack	50
Package in Units	500
T&B Sold in UOM	Each
T&B Weight Per UOM	0.02 lbs. Each

### Application Support

PMA Reference Guide	Available on Website
Product Overview-PMAFIX Connectors	Available on Website
	Available on Website

PMAFIX Connectors-Safety and Sealing  
Systems

**Certifications**

RoHS Compliance	Yes
-----------------	-----

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com