



Family

Catalog Number: LLPA-12A.50
Product ID: 7TAA292030R0005
UPC Number: 78620995766
EAN Number: 07630030250231
Status: Active

Fine Profile Medium-Wall Very Flexible Black Conduit, (LLPA) Material - Polyamide 6, Conduit Size NW - 12, 50 Meters

- Good impact resistance also at low temperatures and dry conditions
- Self-extinguishing
- Free from halogens and cadmium
- Good flexibility
- Renewable Energy
- Technology

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	PMA
Type	Medium Wall Conduit
Application	Machine
Trade Size	NW12
Outside Diameter	0.62 Inch
Inside Diameter	0.47 Inch
Length	50 m
Flexibility	Very Flexible
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	16mm
Outer diameter	15.8mm
Inner diameter	12mm
Material	Polyamide 6
Compressive strength	150N
Operating temperature	-40 - +105°C
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Closable (two-part)	N
Halogen free	Y
Approved according to DIN EN 61386-23	Y
Approved according to UR	Y
Approved according to CSA	Y
Approved according to LUL/British Standard	N
Approved according to Lloyd's Register TA	Y
Approved according to UTAC	N
Approved according to DIN 5510	N
Approved according to NF F 16-101	N

Packaging

Inner Quantity	1
Outer Quantity	20
Outer Dimensions (inches)	47.244x31.496x29.528
Weight Uom	4.4 lbs. Each

Documents / Support Tools

Video US	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com