



Family

Catalog Number: LLPA-23A.50
Product ID: 7TAA292030R0009
UPC Number: 78620995770
EAN Number: 07630030250118
Status: Active

Fine Profile Medium-Wall Very Flexible Black Conduit, (LLPA) Material - Polyamide 6, Conduit Size NW - 23, 50 Meters

- Good impact resistance also at low temperatures and dry conditions
- Self-extinguishing
- Free from halogens and cadmium
- Good flexibility
- Renewable Energy
- Technology

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	PMA
Type	Medium Wall Conduit
Application	Machine
Trade Size	NW23
Outside Diameter	1.12 Inch
Inside Diameter	0.89 Inch
Length	50 Meters
Flexibility	Very Flexible
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	25mm
Outer diameter	28.5mm
Inner diameter	22.6mm
Material	Polyamide 6
Compressive strength	150N
Operating temperature	-40 - +105°C
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Closable (two-part)	N
Halogen free	Y
Approved according to DIN EN 61386-23	Y
Approved according to UR	Y
Approved according to CSA	Y
Approved according to LUL/British Standard	N
Approved according to Lloyd's Register TA	Y
Approved according to UTAC	N
Approved according to DIN 5510	N
Approved according to NF F 16-101	N

Packaging

Inner Quantity	1
Outer Quantity	10
Outer Dimensions (inches)	47.244x31.496x29.528
Weight Uom	11.6 lbs. Each

Documents / Support Tools

Video US 1	Available on Website
------------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com