## Thomas@Betts



Family

 Catalog Number:
 LLPA-36A.30

 Product ID:
 7TAA292030R0013

 UPC Number:
 78620995774

 EAN Number:
 07630030250040

Status: Active

Fine Profile Medium-Wall Very Flexible Black Conduit, (LLPA) Material - Polyamide 6, Conduit Size NW - 36, 30 Meters

- Good impact resistance also at low temperatures and dry conditions
- · Self-extinguishing
- Free from halogens and cadmium
- · Good flexibility
- Renewable Energy
- Technology

| North American Specifications (UNSPSC) |                             |  |
|--|-----------------------------|--|
| UNSPSC                                 | 39131706 Electrical conduit |  |
| IGCC                                   | 5535 Electrical conduit     |  |
| Brand Name                             | PMA                         |  |
| Туре                                   | Medium Wall Conduit         |  |
| Application                            | Machine                     |  |
| Trade Size                             | NW36                        |  |
| Outside Diameter                       | 1.67 Inch                   |  |
| Inside Diameter                        | 1.44 Inch                   |  |
| Length                                 | 30 m                        |  |
| Flexibility                            | Very Flexible               |  |
| Material                               | Polyamide/Nylon 6           |  |
| Color                                  | Black                       |  |

| European Specifications (ETIM)          |                                  |  |
|---|----------------------------------|--|
| ETIM                                    | EC001175 Corrugated plastic hose |  |
| Nominal diameter                        | 40mm                             |  |
| Outer diameter                          | 42.5mm                           |  |
| Inner diameter                          | 36.5mm                           |  |
| Material                                | Polyamide 6                      |  |
| Compressive strength                    | 150N                             |  |
| Operating temperature                   | -40 - +105°C                     |  |
| UV resistant                            | Υ                                |  |
| Colour                                  | Black                            |  |
| Sheathing material                      | Not sheathed                     |  |
| Bending strength                        | Flexible                         |  |
| Lengthwise slotted                      | N                                |  |
| Closable (two-part)                     | N                                |  |
| Halogen free                            | Υ                                |  |
| Approved according to DIN EN 61386-23   | Υ                                |  |
| Approved according to UR                | Υ                                |  |
| Approved according to CSA               | Υ                                |  |
| Approved according to LUL/British Stan- | N                                |  |
| dard                                    |                                  |  |
| Approved according to Lloyd's Register  | Υ                                |  |
| TA                                      |                                  |  |
| Approved according to UTAC              | N                                |  |
| Approved according to DIN 5510          | N                                |  |
| Approved according to NF F 16-101       | N                                |  |



| Packaging                 |                      |
|---------------------------|----------------------|
| Inner Quantity            | 1                    |
| Outer Quantity            | 6                    |
| Outer Dimensions (inches) | 47.244x31.496x29.528 |
| Weight Uom                | 11.6 lbs. Each       |

## **Documents / Support Tools**

Video US Available on Website

## For further technical assistance, please contact us...

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com