



Family

Catalog Number: PCLG-23B.50
Product ID: 7TAA292240R0062
UPC Number: 78620996678
EAN Number: 07630030269462
Status: Active

Coarse Profile Medium Wall Very Flexible Black Conduit, (PCL) Material - Polyamide 6, Conduit Size NW - 23, 50 Meters

- Very good flexibility
- Good mechanical strength at low temperatures and dry conditions
- Self-extinguishing
- Free from halogens and cadmium
- Machine building, installation and vehicle building applications

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	PMA
Type	Medium Wall Conduit
Application	Machine
Standard	CSA
Trade Size	NW23
Outside Diameter	1.12 Inch
Length	50 Meters
Flexibility	Very Flexible
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	25mm
Outer diameter	28.5mm
Inner diameter	21.9mm
Material	Polyamide 6
Compressive strength	150N
Operating temperature	-50 - +105°C
Fire resistance in accordance with UL94	V2
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Closable (two-part)	N
Halogen free	Y
Approved according to DIN EN 61386-23	N
Approved according to UR	Y
Approved according to CSA	Y
Approved according to LUL/British Standard	Y
Approved according to Lloyd's Register TA	Y
Approved according to UTAC	N
Approved according to DIN 5510	N
Approved according to NF F 16-101	N

Packaging

Inner Quantity	1
Outer Quantity	10
Outer Dimensions (inches)	47.244x31.496x29.528
Weight Uom	12.3 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com