



Family

**Catalog Number:** VAMG-23B.50  
**Product ID:** 7TAA292240R0197  
**UPC Number:** 78620997652  
**EAN Number:** 07630030285158  
**Status:** Active

Heavy Wall, Flexible Black Conduit, (VAM) Material - Polyamide 6, Conduit Size NW - 23, 50 Meters

- Good resistance to ultra violet rays and weathering
- High impact and compression strength
- High stiffness
- Outstanding self-extinguishing characteristics
- Minimal development of smoke and gases
- Free from halogens and cadmium
- Renewable Energy
- Rail
- In passenger areas of railway vehicles
- Public buildings to include hospitals, hotels, airports, train and subway stations and shopping centers

#### North American Specifications (UNSPSC)

|                  |                             |
|------------------|-----------------------------|
| UNSPSC           | 39131706 Electrical conduit |
| IGCC             | 5535 Electrical conduit     |
| Brand Name       | PMA                         |
| Type             | Heavy Duty Conduit          |
| Application      | Machine                     |
| Trade Size       | NW23                        |
| Outside Diameter | 1.12 Inch                   |
| Length           | 50 m                        |
| Flexibility      | Medium Flexibility          |
| Material         | Polyamide/Nylon 6           |
| Color            | Black                       |

#### European Specifications (ETIM)

|  |                                  |
|--|----------------------------------|
| ETIM                                       | EC001175 Corrugated plastic hose |
| Nominal diameter                           | 25mm                             |
| Outer diameter                             | 28.5mm                           |
| Inner diameter                             | 22mm                             |
| Material                                   | Polyamide 6                      |
| Compressive strength                       | 350N                             |
| Operating temperature                      | -40 - +105°C                     |
| UV resistant                               | Y                                |
| Colour                                     | Black                            |
| Sheathing material                         | Not sheathed                     |
| Bending strength                           | Flexible                         |
| Lengthwise slotted                         | N                                |
| Closable (two-part)                        | N                                |
| Halogen free                               | Y                                |
| Approved according to DIN EN 61386-23      | N                                |
| Approved according to UR                   | N                                |
| Approved according to CSA                  | N                                |
| Approved according to LUL/British Standard | N                                |
|  | Y                                |

Approved according to Lloyd's Register  
TA

|                                   |   |
|-----------------------------------|---|
| Approved according to UTAC        | N |
| Approved according to DIN 5510    | Y |
| Approved according to NF F 16-101 | N |

**Packaging**

|                           |                      |
|---------------------------|----------------------|
| Inner Quantity            | 1                    |
| Outer Quantity            | 10                   |
| Outer Dimensions (inches) | 47.244x31.496x30.709 |
| Weight Uom                | 14.61 lbs. Each      |

**Documents / Support Tools**

Technical Drawing / Data Sheet Canada Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)