
+

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

NOTES:

- 1. DIAMETER DIMENSION, SHOWN FOR REFERENCE ONLY.
- 2. DIMENSIONS IN BRACKETS [] ARE ENGLISH.
- 3. ALL MATERIALS AND COMPONENTS USED MUST MEET THE MATERIAL RESTRICTIONS OF ROHS (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE ROHS TECHNICAL ADAPTATION COMMITTEE.



TECHNICAL SPECIFICATIONS								
MAXIMUM LOS	SS	SINGLEMODE MAXIMUM LOSS						
3.5 dB/KM @ 8 1.5 dB/KM @ 13		.40 dB/KM @ l3l0nm .30 dB/KM @ l500nm						
BEND RADIUS								
INSTALLAT	ION	LONG TERM						
42.4cm [16.6in	1	21.2cm [8.3in]						
TENSILE LOAD								
INSTALLAT	ION	l I	LONG TERM					
2700 N (600 lbf)	1	890 N (200 lbf)						
TEMPERATURE								
INSTALLATION	OPER/	ATION	STORAGE					
-30°C TO +60°C -22°F TO +140°F		O +70°C) +158°F	-40°C TO +75°C -40°F TO +167°F					

REV	DATE	ВҮ	СНК	DESCRIPTION	ECN -	R	CUST	SUP	ОТН	CHK.D MWW		02055-161 SHEET 1 OF 2 A	
02	10-29-09	EFK		RELEASED TO PRODUCTION	02055-161				·	07 - 10 - 07		DRAWING NO. SIZE	
										DRAWN BY EFK	REVIEW DRAWING NUMBERS	FSWN*IA FOWN*IA	
										THIRD ANGLE PROJECTION	(.XX) ±0.8 (.03) ANGLES	NONL	
											UNLESS OTHERWISE SPECIFIED.	DRAWING FILENAME MO2055DA_DC_144/00C	
											TINLEY PARK, ILL		
												_⊠ ТМ	
										CUSTOMER DRAWING			
										OUTSIDE PLANT SINGLE ARMOR-SINGLE JACKET CABLE WITH (12) 12 FIBER SUB-UNITS			

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART NUMBER	FIBER TYPE	FIBER COUNT	TUBE COUNT	DIAMETER
FSWN91A	SINGLEMODE 9/125um			
FSWN61A	MULTIMODE 62.5/125um			
FSWN51A	MULTIMODE 50/125um	144	12 WITH 12 FIBERS	21.2mm [0.83"]
FOWNXIA	MULTIMODE 50/125um OM3			
FOWNZIA	MULTIMODE 50/125um OM4			

REV	DATE	BY	СНК	DESCRIPTION	ECN -	R	CUST	SUP	отн	WMA		SHEET 2 OF 2
02	10-29-09	EFK		RELEASED TO PRODUCTION	02055-161					07 - 10 - 07		02055-161 A
										DRAWN BY EFK	REVIEW DRAWING NUMBERS	FSWN*IA FOWN*IA
										TILLED ANCLE	(.XX) ±0.8 (.03) ANGLES	NONE
											ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:	DRAWING FILENAME MO2055DA_DC_144/00C
											TINLEY PARK, ILL	CORP. 60477
												TM
										CABLE WITH (12) 12 FIBER SUB-UNITS CUSTOMER DRAWING		
											PLANT SINGLE ARMO	