



Industrial Electrical Infrastructure

Preferred Parts – Middle East

PANDUIT[™]
infrastructure for a connected world

Industrial Electrical Infrastructure

Partner with a company committed to meeting the challenges you face when designing, installing and maintaining cabling infrastructures within heavy-duty industrial environments. Our global distribution, manufacturing, sales and technical support teams make Panduit solutions readily accessible, allowing the right products to be delivered when and where they are needed.

This catalog features the most common offering for heavy-duty industrial environments. For the complete offering, please contact your local Panduit representative or visit us at www.panduit.com/buildnow.



Table of Contents

Computer Printables	3
Labeling Systems	4
Loose Piece Cable Ties	5 – 6
Stainless Steel Cable Ties and Permanent Identification	6 – 7
Terminals	7

Computer Printables



Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
H200X034H1T	Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.34"H, White, 500 pieces.	1	—
H200X034H1T-B	Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.34"H, White, 2500 pieces.	1	—
H200X044H1T	Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.44"H, White, 500 pieces.	1	—
H200X044H1T-B	Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.44"H, White, 2500 pieces.	1	—
H200X064H1T	Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.64"H, White, 500 pieces.	1	—
H200X064H1T-B	Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.64"H, White, 500 pieces.	1	—
M300X050Y7T	Thermal transfer, marker plate, polyester/polyolefin, 3.00"W x 1.00"H, White.	1	4
M300X100Y6T	Thermal transfer, marker plate, polyester/polyolefin, 3.00"W x 1.00"H, Yellow.	1	4
M300X100Y7T	Thermal transfer, marker plate, polyester/polyolefin, 3.00"W x 1.00"H, White.	1	4
NWSLC-3Y	Orange cable identification sleeve for 3mm simplex cable, 1" length, 100 per pack.	100	1000
NWSLC-7Y	White cable identification sleeve for 3mm duplex fiber cable, 1" length, 100 per pack.	100	1000
PES197/E	Portable embossing system, 0.187" (4.77mm), 230 volts.	1	—
RMH4BL	Ribbon, hybrid, 4" wide, for use with TDP43MY and PTR2E, Black.	1	—
S050X075VATY	Thermal transfer, self-laminating label, vinyl, 0.50"W x 0.75"H, 0.25" print-on area, Clear/White, 3" core.	5000	40000
S100X150YAJ	Laser/inkjet, self-laminating label, polyester, 1.00"W x 1.50"L, 0.50" print-on area, Clear/White.	2500	10000
S100X160YAJ	Laser, self-laminating label, polyester, 1.00"W x 1.60"H, 0.80" print-on area, Clear/White.	2500	10000
S100X225YAJ	Laser, self-laminating label, polyester, 1.00"W x 2.25"L, 0.75" print-on area, Clear/White.	1000	5000
S100X400VA1Y	Thermal transfer, self-laminating label, vinyl, 1.00"W x 4.00"H, 1.00" print-on area, Clear/White, 1" core.	1000	4000
S200X150YAJ	Laser/inkjet, self-laminating label, polyester, 2.00"W x 1.50"H, 0.50" print-on area, Clear/White.	1000	5000
S200X225YAJ	Laser, self-laminating label, polyester, 2.00"W x 2.25"L, 0.75" print-on area, Clear/White.	1000	5000
TDP43ME/E	300 dpi printer, including Easy-Mark™ Labeling Software and RMEH4BL hybrid ribbon.	1	—



PES197/E



TDP43ME/E

Labeling Systems



Thermal Transfer Continuous Tape

Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
T400X000YK1	Thermal transfer, continuous tape, polyester, 4.00"W x 100'L, Clear, 1" core.	1	4
T400X000VY1Y	Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Black, 1" core.	1	4
T400X000VX1Y	Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Yellow, 1" core.	1	4
T400X000VW1Y	Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Red, 1 inch core.	1	4
T400X000VU1Y	Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Orange, 1" core.	1	4
T400X000VS1Y	Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Green, 1" core.	1	4
T400X000VQ1Y	Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, Blue, 1" core.	1	4
T400X000VP1Y	Thermal transfer, continuous tape, vinyl, 4.00"W x 100'L, White, 1" core.	1	4
T200X000YK1	Thermal transfer, continuous tape, polyester, 2.00"W x 100'L, Clear, 1" core.	1	4
T200X000VY1Y	Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Black, 1" core.	1	4
T200X000VX1Y	Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Yellow, 1" core.	1	4
T200X000VW1Y	Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Red, 1" core.	1	4
T200X000VU1Y	Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Orange, 1" core.	1	4
T200X000VS1Y	Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Green, 1" core.	1	4
T200X000VQ1Y	Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, Blue, 1" core.	1	4
T200X000VP1Y	Thermal transfer, continuous tape, vinyl, 2.00"W x 100'L, White, 1" core.	1	4
T100X000YK1	Thermal transfer, continuous tape, polyester, 1.00"W x 100'L, Clear, 1" core.	1	4
T100X000VY1Y	Thermal transfer, continuous tape, vinyl, 1.00"W x 100'L, Black, 1" core.	1	4
T100X000VXC-BK	P1™ Cassette, continuous tape, vinyl, 1.00"W x 25'L, Yellow/Black.	1	10
T100X000VX1Y	Thermal transfer, continuous tape, vinyl, 1.00"W x 100'L, Yellow, 1" core.	1	4
T100X000VW1Y	Thermal transfer, continuous tape, vinyl, 1.00"W x 100'L, Red, 1" core.	1	4
T100X000VUC-BK	P1™ Cassette, continuous tape, vinyl, 1.00"W x 25'L, Orange/Black.	1	10
T100X000VU1Y	Thermal transfer, continuous tape, Vinyl, 1.00"W x 100'L, Orange, 1" core.	1	4
T100X000VS1Y	Thermal transfer, continuous tape, Vinyl, 1.00"W x 100'L, Green, 1" core.	1	4
T100X000VQ1Y	Thermal transfer, continuous tape, Vinyl, 1.00"W x 100'L, Blue, 1" core.	1	4
T100X000VPC-BK	P1™ Cassette, continuous tape, vinyl, 1.00"W x 25'L, Black on White.	1	10
T100X000VP1Y	Thermal transfer, Continuous Tape, Vinyl, 1.00"W x 100'L, White, 1" core.	1	4
T075X000VPC-BK	P1™ Cassette, continuous tape, vinyl, 0.75"W x 25'L, Black on White.	1	10
T050X000VXC-BK	P1™ Cassette, continuous tape, vinyl, 0.50"W x 25'L, Yellow/Black.	1	10
T050X000VPC-BK	P1™ Cassette, continuous tape, vinyl, 0.50"W x 25'L, Black on White.	1	10
T038X000VPC-BK	P1™ Cassette, continuous tape, vinyl, 0.38"W x 25'L, Black on White	1	10
T038X000FJC-BK	P1™ Cassette, continuous tape, polyolefin, 0.38"W x 25'L, White/Black.	1	10
S100X225VAC	P1™ Cassette, self-laminating label, vinyl, 1.00"W x 2.25"H, 0.75" print-on area, Clear/White.	1	10
S100X150VAC	P1™ Cassette, self-laminating label, vinyl, 1.00"W x 1.50"H, 0.50" print-on area, Clear/White.	1	10
S100X075VAC	P1™ Cassette, self-laminating label, vinyl, 1.00"W x 0.75"H, 0.25" print-on area, Clear/White.	1	10
R100X225V1C	P1™ Cassette, self-laminating label, vinyl, 1.00" W x 2.25" H, 0.75" print-on area, Clear/White	1	10
R100X150V1C	P1™ Cassette, Turn-Tell™ Self-Laminating Label, vinyl, 1.00"W x 1.50"H, 0.50" print-on area, Clear/White	1	10
M300X050Y6T	Thermal transfer, marker plate, polyester/polyolefin, 3.00"W x .50"H, Yellow.	1	—
M300X050Y6C	P1™ Marker Plate 3"W x 0.50"H, Yellow.	1	10
H200X084H2T	Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.84"H, Yellow, 500 pieces.	1	—
H200X044H2T	Thermal transfer, heat shrink tubing, Military grade polyolefin, 2.00"W x 0.44"H, Yellow, 500 pieces.	1	—
H100X034H1C	P1™ Cassette, heat shrink tubing, Military grade polyolefin, 1.00"W x 0.34"H, White.	1	10
H000X084H1C	P1™ Cassette, continuous heat shrink tubing, Military grade polyolefin, 6"W x 0.84"H, White.	1	10
H000X034H1C	P1™ Cassette, continuous heat shrink tubing, Military grade polyolefin, 8"W x 0.34"H, White.	1	10
F100X150AJC	P1™ Cassette, flag label, polyester, 1.00"W x 1.50"H.	1	10
C252X030FJC	P1™ Cassette, network label, adhesive polyolefin, 2.52"W x .30"H, White.	1	10
S8EQ-KIT-ACE	LS8EQ QWERTY hand-held thermal transfer printer kit with AC power adapter for Europe.	1	2
LS8EQ-KIT	QWERTY LS8EQ, printer kit.	1	2
LS8EQ	QWERTY LS8E, printer.	1	4
LS8E-KIT	LS8E, printer kit.	1	2
LS8E	LS8E, Printer	1	4



LS8EQ-KIT

Loose Piece Cable Ties



PLT Ties



Barb Ties

Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
PLT3I-C0	11.4"L (290mm), Intermediate, weather resistant, Black.	100	1000
PLT3H-L0	11.4"L (290mm), Light-Heavy, weather resistant, Black.	50	500
PLT3S-C0	11.5"L (292mm) Standard, weather resistant, Black.	100	1000
PLT4I-C0	14.5"L (368mm), Intermediate, weather resistant, Black.	100	1000
PLT4H-L0	14.5"L (368mm), Light-Heavy, weather resistant, Black.	50	500
PLT4H-TL0	14.5"L (368mm), Light-Heavy, weather resistant, Black.	250	2500
PLT4S-M120	14.5"L (368mm), Standard, nylon 12, Black.	1000	5000
PLT4S-C0	14.5"L (368mm), Standard, weather resistant, Black.	100	1000
PLT4S-M0	14.5"L (368mm), Standard, weather resistant, Black.	1000	5000
PLT4.5S-C0	15.5"L (394mm), Standard, weather resistant, Black.	100	1000
PLT5S-M0	17.5"L (445mm), Standard, weather resistant, Black.	1000	5000
PLT5H-L0	17.7"L (450mm), Heavy, weather resistant, Black.	50	500
PLT6H-C0	20.9"L (530mm), Heavy, weather resistant, Black.	100	1000
PLT6H-L0	20.9"L (530mm), Heavy, weather resistant, Black.	50	500
PLT6LH-L0	21.9"L (556mm), Light-Heavy, weather resistant, Black.	50	500
PLT7LH-L0	24.7"L (627mm), Light-Heavy, weather resistant, Black.	50	500
PLT8LH-C120	27.6"L (701mm), Light-Heavy, nylon 12, Black.	100	1000
PLT8LH-L0	27.6"L (701mm), Light-Heavy, weather resistant, Black.	50	500
PLT1M-C	3.9"L (99mm), Miniature, nylon, Natural.	100	1000
PLT1M-C0	3.9"L (99mm), Miniature, weather resistant, Black.	100	1000
PLT1M-M0	3.9"L (99mm), Miniature, weather resistant, Black.	1000	50000
PLT8H-C0	30.6"L (779mm), Heavy, weather resistant, Black.	100	1000
PLT1.5I-M30	5.6"L (142mm), Intermediate, heat stabilized, Black.	1000	25000
PLT1.5I-M120	5.6"L (142mm), Intermediate, nylon 12, Black.	1000	25000
PLT1.5I-M0	5.6"L (142mm), Intermediate, weather resistant, Black.	1000	25000
PLT1.5M-C0	5.6"L (142mm), Miniature, weather resistant, Black.	100	1000
PLT2S-M120	7.4"L (188mm), Standard, nylon 12, Black.	1000	10000
PLT2S-C0	7.4"L (188mm), Standard, weather resistant, Black.	100	1000
PLT2S-M0	7.4"L (188mm), Standard, weather resistant, Black.	1000	10000
PLT2M-C	8.0"L (203mm), Miniature, nylon, Natural.	100	1000
PLT2M-C0	8.0"L (203mm), Miniature, weather resistant, Black.	100	1000
BT3I-C0	Metal barb, 11.3"L (287mm), Intermediate, weather resistant, Black.	100	1000
BT3LH-L0	Metal barb, 11.8"L (300mm), Light-Heavy, weather resistant, Black.	50	500
BT3S-C	Metal barb, 12.0"L (305mm), Standard, nylon, Natural.	100	1000
BT3S-C0	Metal barb, 12.0"L (305mm), Standard, weather resistant, Black.	100	1000
BT4M-C0	Metal barb, 14.2"L (361mm), Miniature, weather resistant, Black.	100	1000
BT4S-C0	Metal barb, 15.1"L (384mm), Standard, weather resistant, Black.	100	1000
BT5LH-L0	Metal barb, 18.1"L (460mm), Light-Heavy, weather resistant, Black.	50	500
BT7LH-C0	Metal barb, 24.4"L (620mm), Light-Heavy, weather resistant, Black.	100	1000
BT7LH-L0	Metal barb, 24.4"L (620mm), Light-Heavy, weather resistant, Black.	50	500
BT1M-C	Metal barb, 4.0"L (102mm), Miniature, nylon, Natural.	100	1000
BT1.5I-C0	Metal barb, 6.1"L (155mm), Intermediate, weather resistant, Black.	100	1000
BT2M-C	Metal barb, 7.9"L (201mm), Miniature, nylon, Natural.	100	1000
BT2M-C0	Metal barb, 7.9"L (201mm), Miniature, weather resistant, Black.	100	1000
BT2I-C0	Metal barb, 8.0"L (203mm), Intermediate, weather resistant, Black.	100	1000
BT2I-M0	Metal barb, 8.0"L (203mm), Intermediate, weather resistant, Black.	1000	25000
BT2S-C0	Metal barb, 8.0"L (203mm), Standard, weather resistant, Black.	100	1000

(continued on page 6)

Loose Piece Cable Ties (continued)



GS2B



GS4H



GTS

Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
P12-40-C	Nylon 6.6, 11.8"L, 0.87" maximum bundle diameter.	100	1000
P12-40-C0	Weather resistant nylon 6.6, 11.8"L, 0.87" maximum bundle diameter.	100	1000
P12-50-C	Nylon 6.6, 11.8"L, 2.99" maximum bundle diameter.	100	1000
P12-50-C0	Weather resistant nylon 6.6, 11.8"L, 2.99" maximum bundle diameter.	100	1000
P14-120-L	Nylon 6.6, 14.5"L, 4.02" maximum bundle diameter.	50	500
P14-120-L0	Weather resistant nylon 6.6, 14.5"L, 4.02" maximum bundle diameter.	50	500
P14-40-C	Nylon 6.6, 14.6"L, 4.02" maximum bundle diameter.	100	1000
P14-40-C0	Weather resistant nylon 6.6, 14.6"L, 4.02" maximum bundle diameter.	100	1000
P14-50-C	Nylon 6.6, 14.6"L, 4.02" maximum bundle diameter.	100	1000
P14-50-C0	Weather resistant nylon 6.6, 14.6"L, 4.02" maximum bundle diameter.	100	1000
P4-18-C	Nylon 6.6, 3.9"L, 0.87" maximum bundle diameter.	100	1000
P4-18-C0	Weather resistant nylon 6.6, 3.9"L, 0.87" maximum bundle diameter.	100	1000
P5-18-C	Nylon 6.6, 5.5"L, 1.30" maximum bundle diameter.	100	1000
P5-18-C0	Weather resistant nylon 6.6, 5.5"L, 1.30" maximum bundle diameter.	100	1000
P5-40-C	Nylon 6.6, 5.5"L, 1.30" maximum bundle diameter.	100	1000
P5-40-C0	Weather resistant nylon 6.6, 5.5"L, 1.30" maximum bundle diameter.	100	1000
P7-50-C	Nylon 6.6, 7.4"L, 1.81" maximum bundle diameter.	100	1000
P7-50-C0	Weather resistant nylon 6.6, 7.4"L, 1.81" maximum bundle diameter.	100	1000
P8-18-C	Nylon 6.6, 7.9"L, 2.09" maximum bundle diameter.	100	1000
P8-18-C0	Weather resistant nylon 6.6, 7.9"L, 2.09" maximum bundle diameter.	100	1000
P8-40-C	Nylon 6.6, 7.9"L, 2.09" maximum bundle diameter.	100	1000
P8-40-C0	Weather resistant nylon 6.6, 7.9"L, 2.09" maximum bundle diameter.	100	1000
PC15-120-S25-L	Nylon 6.6, 15"L, 3.86" maximum bundle diameter.	50	500
PC15-120-S25-L0	Weather resistant nylon 6.6, 15"L, 3.86" maximum bundle diameter.	50	500
PC8-50-S10-C	Nylon 6.6, 7.9"L, 1.97" maximum bundle diameter.	100	1000
PC8-50-S10-C0	Weather resistant nylon 6.6, 7.9"L, 1.97" maximum bundle diameter.	100	1000
PM4-18-C	Nylon 6.6, 3.9"L, 0.71" maximum bundle diameter.	100	1000
PM7-50-C	Nylon 6.6, 7.5"L, 1.81" maximum bundle diameter.	100	1000
PR12-50-C	Nylon 6.6, 11.8"L, 2.99" maximum bundle diameter.	100	1000
PR12-50-C0	Weather resistant nylon 6.6, 11.8"L, 2.99" maximum bundle diameter.	100	1000
PR8-50-C	Nylon 6.6, 7.9"L, 1.97" maximum bundle diameter.	100	1000
PR8-50-C0	Weather resistant nylon 6.6, 7.9"L, 1.97" maximum bundle diameter.	100	1000
GS2B	Cable tie tool for Miniature, Intermediate, and Standard ties, adjustable tension.	1	—
GS4H	Cable tie tool for Standard, Heavy-Standard, Light-Heavy, and Heavy ties, adjustable tension.	1	—
GTS	Ergonomic cable tie tool for Subminiature, Miniature, Intermediate, and Standard ties, adjustable tension.	1	—

Stainless Steel Cable Ties and Permanent Identification



MLT Ties

Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
MLT10H-LP	MLT tie, 304 stainless steel, Heavy, 33.0" (838mm), 0.010" (0.25mm) thickness.	50	250
MLT1S-CP	MLT tie, 304 stainless steel, Standard, 5.0" (127mm), 0.010" (0.25mm) thickness.	100	500
MLT1S-CP316	MLT tie, 316 stainless steel, Standard, 5.0" (127mm), 0.010" (0.25mm) thickness.	100	500
MLT2.7S-CP	MLT tie, 304 stainless steel, Standard, 10.2" (259mm), 0.010" (0.25mm) thickness.	100	500
MLT2S-CP	MLT tie, 304 stainless steel, Standard, 7.9" (201mm), 0.010" (0.25mm) thickness.	100	500
MLT2S-CP316	MLT tie, 316 stainless steel, Standard, 7.9" (201mm), 0.010" (0.25mm) thickness.	100	500
MLT4H-LP	MLT tie, 304 stainless steel, Heavy, 14.3" (362mm), 0.010" (0.25mm) thickness.	50	250
MLT4S-CP	MLT tie, 304 stainless steel, Standard, 14.3" (362mm), 0.010" (0.25mm) thickness.	100	500
MLT4S-CP316	MLT tie, 316 stainless steel, Standard, 14.3" (362mm), 0.010" (0.25mm) thickness.	100	500
MLT6H-LP	MLT tie, 304 stainless steel, Heavy, 20.5" (521mm), 0.010" (0.25) thickness.	50	250

(continued on page 7)

Stainless Steel Cable Ties and Permanent Identification (continued)

Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
MLTC2H-LP316	MLT tie, 316 stainless steel, selectively coated, Heavy, 7.9" (201mm), 0.010" (0.25mm) thickness.	50	250
MLTC4H-LP316	MLT tie, 316 stainless steel, selectively coated, Heavy, 14.3" (362mm), 0.010" (0.25mm) thickness.	50	250
MLTC6H-LP316	MLT tie, 316 stainless steel, selectively coated, Heavy, 20.5" (521mm), 0.010" (0.25mm) thickness.	50	250
MLTFC1.5S-CP316	MLT tie, 316 stainless steel, fully coated, Standard.	100	500
MLTFC2S-CP316	MLT tie, 316 stainless steel, fully coated, Standard, 7.9" (201mm), 0.010" (0.25mm) thickness.	100	500
MLTFC4H-LP316	MLT tie, 316 stainless steel, fully coated, Heavy, 14.3" (362mm), 0.010" (0.25mm) thickness.	50	250
MLTFC4S-CP316	MLT tie, 316 stainless steel, fully coated, Standard, 14.3" (362mm), 0.010" (0.25mm) thickness.	100	500
MLTFC5.4H-CP316	MLT tie, 316 stainless steel, fully coated, Heavy, 18" (457mm), 0.010" (0.25mm) thickness.	100	500
MLTFC6H-LP316	MLT tie, 316 stainless steel, fully coated, Heavy, 20.5" (521mm), 0.010" (0.25mm) thickness.	50	250
MLTFC8H-LP316	MLT tie, 316 stainless steel, fully coated, Heavy, 26.8" (679mm), 0.010" (0.25mm) thickness.	50	250
MLTFC8S-CP316	MLT tie, 316 stainless steel, fully coated, Standard, 26.8" (679mm), 0.010" (0.25mm) thickness.	100	500
MEHT187	Metal tape embossing tool.	1	—
METS3-X	Embossing tape, 316 stainless steel, 0.5" X 21' (12.7mm x 6.4m).	10	40
METS4-X	Embossing tape, 304 stainless steel, 0.5" X 21' (12.7mm x 6.4m).	10	40
MMP350-C316	Marker plate, 316 stainless steel, four-hole 3.5" x 0.75" x 0.010" (89mm x 19mm x 0.25mm) thickness.	100	1000
MMP350H-C	Marker plate, 304 stainless steel, four-hole, 3.5" x 0.75" x 0.010" (89mm x 19mm x 0.25mm) thickness.	100	1000
MMP350H-C316	Marker plate, 316 stainless steel, four-hole, 3.5" x 0.75" x 0.010" (89mm x 19mm x 0.25mm) thickness.	100	1000
MMP350H-M316	Marker plate, 316 stainless steel, four-hole, 3.5" x 0.75" x 0.010" (89mm x 19mm x 0.25mm) thickness.	1000	4000
ST2MT	Installation tool, MLT ties, twist cut off, Light-Heavy and Super-Heavy cross section.	1	—
GS4MT	Installation tool, MLT ties, controlled tension gun style, Standard. Light-Heavy, Heavy cross section.	1	—



MEHT187



MMP350-C



ST2MT



GS4MT

Terminals

Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
PV18-6FX-MY	Fork terminal, expanded vinyl, 22 – 18 AWG, #6 stud size.	1000	6000
PV14-10F-C	Fork terminal, vinyl insulated, 16 – 14 AWG, #10 stud size.	100	500
PV14-8F-C	Fork terminal, vinyl insulated, 16 – 14 AWG, #8 stud size.	100	500
PV18-10F-MY	Fork terminal, vinyl insulated, 22 – 16 AWG, #10 stud size.	1000	—
PV18-8F-CY	Fork terminal, vinyl insulated, 22 – 16 AWG, #8 stud size.	100	500
PV10-8LF-L	Locking fork terminal, vinyl insulated, 12 – 10 AWG, #8 stud size.	50	500
PV14-6LF-M	Locking fork terminal, vinyl insulated, 18 – 14 AWG, #6 stud size.	1000	6000
PV14-8LF-M	Locking fork terminal, vinyl insulated, 18 – 14 AWG, #8 stud size.	1000	—
PV18-6LF-CY	Locking fork terminal, vinyl insulated, 22 – 18 AWG, #6 stud size.	100	500
PN10-10R-D	Ring terminal, nylon insulated, 12 – 10 AWG, #10 stud size.	500	—
PN10-6R-D	Ring terminal, nylon insulated, 12 – 10 AWG, #6 stud size.	500	—
PN10-38R-D	Ring terminal, nylon insulated, 12 – 10 AWG, 3/8" stud size.	500	—
PN10-56R-D	Ring terminal, nylon insulated, 12 – 10 AWG, 5/16" stud size.	500	3000
PN14-10R-M	Ring terminal, nylon insulated, 18 – 14 AWG, #10 stud size.	1000	—
PN14-8R-M	Ring terminal, nylon insulated, 18 – 14 AWG, #8 stud size.	1000	—
PN18-10R-M	Ring terminal, nylon insulated, 22 – 18 AWG, #10 stud size.	1000	—
PN18-14R-M	Ring terminal, nylon insulated, 22 – 18 AWG, #1/4 stud size.	1000	—
PN18-6R-M	Ring terminal, nylon insulated, 22 – 18 AWG, #6 stud size.	1000	—
PV10-10R-D	Ring terminal, vinyl insulated, 12 – 10 AWG, #10 stud size.	500	—
PV14-14R-M	Ring terminal, vinyl insulated, 16 – 14 AWG, #1/4 stud size.	1000	6000



Fork Terminal



Locking Fork Terminal



Ring Terminal



PANDUIT™

Panduit CBC London
6 Broad Street Place
London
EC2M 7JH
UK
phone +44 (0) 208 601 7200

EMEA-CustomerServices@panduit.com
1-800-PANDUIT

www.panduit.com