

# LED B11

## 5.5B11/PER/927-922/CL/G/E12/WGX 1FB T20

Philips LED B11 candles offer energy saving ambiance with the elegant effect of incandescent candles. These designs provides light in an omnidirectional manner, giving lighting designers a long life alternative to standard incandescent sources.


### Product data

General Information	
Base	E12 [ Candelabra Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	20000X
Technical Type	5,5-60W
Light Technical	
Color Code	927-922 [ CCT of 2700K-2200K]
Initial lumen (Nom)	500 lm
Color Designation	Warm Glow(WG)
Correlated Color Temperature (Nom)	2700-2200 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Power (Rated) (Nom)	5,5 W
Lamp Current (Nom)	60 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0,5 s
Warm Up Time to 60% Light (Nom)	0,5 s

Power Factor (Nom)	0.75
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	60 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Product Data	
XUCDM.COPY.Product.Title	5.5B11/PER/927-922/CL/G/E12/WGX 1FB T20
EAN/UPC - Product	046677549336
Order code	549337
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002204504
Net Weight (Piece)	0.020 kg

# LED B11


## Dimensional drawing




CandlB11120V5.5-60W500lm2700-2200KE12DCL

Product	D	C
5.5B11/PER/927-922/CL/G/E12/WGX 1FB T20	35 mm	100 mm


## Photometric data



LEDbulb E12 E26 BA11 B11 927 CL-LDD





LEDbulb 927 CL-POC



LEDbulb 5.5W E12 B11 927 CL

# LED B11

## Lifetime



LEDbulb\_15K LED

LEDbulb\_15K LMP

