



# T8 900 Series Rapid Start

## F32T8/TL 950 25PK

Philips leads the industry with the lowest level mercury technology. Reducing the mercury level (source reduction) during the manufacturing phase is essential to creating products that are less harmful to the environment.


### Product data

General Information		Color Rendering Index (Nom)	
Cap-Base	G13 [ Medium Bi-Pin Fluorescent]		98
Bulb Shape	T8 [ T8 (T8)]	Operating and Electrical	
Life To 50% Failures (Nom)	15000 h	Power (Rated) (Nom)	31.3 W
Life To 50% Failures Preheat (Nom)	20000 h	Lamp Current (Nom)	0.265 A
Life 3-Hr Start [Hrs]	20000 h	Voltage (Nom)	139 V
Life 12-Hr Start [Hrs]	20000 h	Controls and Dimming	
Light Technical		Dimmable	Yes
Color Code	TL950 [ CCT of 5000K (950)]	Approval and Application	
Initial lumen (Nom)	2000 lm	Energy Efficiency Label (EEL)	B
Color Designation	TL950	Mercury (Hg) Content (Nom)	5.0 mg
Lumen Maintenance 10000 h (Nom)	84 %	Product Data	
Lumen Maintenance 2000 h (Nom)	90 %	Order product name	F32T8/TL950 SLV
Lumen Maintenance 5000 h (Nom)	89 %	EAN/UPC - Product	046677209056
Design Mean Lumens	1860 lm	Order code	209056
Chromaticity Coordinate X (Nom)	342	Numerator - Quantity Per Pack	1
Chromaticity Coordinate Y (Nom)	352	Numerator - Packs per outer box	25
Correlated Color Temperature (Nom)	5000 K		
Luminous Efficacy (rated) (Nom)	63.9 lm/W		

## T8 900 Series Rapid Start

Material Nr. (12NC)	927942009520
Net Weight (Piece)	137.500 g

### Dimensional drawing



#### Product

F32T8/TL950 SLV

F32T8/TL950

