



# Pulse Start Metal Halide Standard

## MS250/BU/PS 12PK

Philips Pulse Start Metal Halide Lamps offer an optimized metal halide system for greater efficiency and lumen maintenance.

### Product data

General Information	
Cap-Base	E39 [ Single Contact Mogul Screw ]
Operating Position	Base Up +/- 15 D [ Base Up +/- 15 D ]
Main Application	General Lighting (G)
Life To 50% Failures (Nom)	15000 h
ANSI Code HID	M153/M138/E
System Description	Pulse Start
Light Technical	
Color Code	645 [ CCT of 4500K ]
Luminous Flux (Rated) (Min)	21375 lm
Luminous Flux (Rated) (Nom)	23750 lm
Color Designation	Cool White (CW)
Design Mean Lumens	16625 lm
Chromaticity Coordinate X (Nom)	374
Chromaticity Coordinate Y (Nom)	392
Correlated Color Temperature (Nom)	4300 K
Luminous Efficacy (rated) (Min)	85.5 lm/W
Luminous Efficacy (rated) (Nom)	95 lm/W
Color Rendering Index (Nom)	65

Operating and Electrical	
Lamp Current (Nom)	2 A
Ignition Supply Voltage (Min)	254 V
Re-Ignition Time (Min) (Max)	4 min
Ignition Time (Max)	120 s
Voltage (Max)	147 V
Voltage (Min)	119 V
Voltage (Nom)	133 V
Mechanical and Housing	
Bulb Finish	Clear (CL)
Cap-Base Information	Nic/Brass
Bulb Material	Hard Glass
Approval and Application	
Mercury (Hg) Content (Max)	32.6 mg
UV	
Pet (Niosh) (Nom)	80.8 h/500lx
Damage Factor D/fc (Nom)	0.49

## Pulse Start Metal Halide Standard

### Luminaire Design Requirements

Bulb Temperature (Max)	400 °C
Cap-Base Temperature (Max)	210 °C

### Product Data


Order product name	MS250/BU/PS 12PK
EAN/UPC - Product	046677276614

Order code	276618
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601152203
Net Weight (Piece)	0.001 kg

### Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

### Dimensional drawing



MH PS 250W/645 E39 ED28 BU

Product	D	C
MS250/BU/PS 12PK	3.5 in	8.313 in

