



PAR30/PAR20 LED

12PAR30S/S15 3000 CW SO-B 6/1

Philips PAR30 and PAR20 LED Single Optic Lamps provide superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Bulb Shape	PAR30S [PAR 3.75 inch/95mm Short]
Nominal Lifetime (Nom)	50000 h
Switching Cycle	20000X
Technical Type	12.5-60W

Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	15 °
Light Distribution	15D [Narrow beam]
Initial lumen (Nom)	780 lm
Luminous Flux (Rated) (Nom)	780 lm
Luminous Intensity (Nom)	6300 cd
Color Designation	White (WH)
Rated Beam Angle	15 °
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	62.40 lm/W
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	60 Hz
Power (Rated) (Nom)	12.5 W

Lamp Current (Nom)	115 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.9
Voltage (Nom)	120 V

Controls and Dimming	
Dimmable	No

Approval and Application	
Energy Efficiency Label (EEL)	A
Energy Consumption kWh/1000 h	13 kWh


Product Data	
Order product name	120V PAR30S 12.5W 15D 3000K 780 CW SOB
EAN/UPC - Product	046677434939
Order code	434936
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929001110104
Net Weight (Piece)	0.310 kg

PAR30/PAR20 LED

Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- Before replacing, turn off power and let lamp cool to avoid electrical shock or burn.
- CAUTION: Risk of electric shock— do not use where directly exposed to water
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005.

Dimensional drawing



Product	D	C
120V PAR30S 12.5W 15D 3000K 780 CW SOB	92 mm	93 mm

LED 12.5W E26 3000K 120V PAR30S 15D

