



# PAR30/PAR20 LED

## 12PAR30S/S15 2700 DIM AF SO 6/1

Philips PAR30 and PAR20 LED Single Optic Lamps provide superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

### Product data

General Information	
Cap-Base	E26 [ Single Contact Medium Screw]
Bulb Shape	PAR30S [ PAR 3.75 inch/95mm Short]
Nominal Lifetime (Nom)	25000 h
Switching Cycle	50000X
Technical Type	12-75W

Light Technical	
Color Code	827 [ CCT of 2700K]
Beam Angle (Nom)	15 °
Initial lumen (Nom)	850 lm
Luminous Flux (Rated) (Nom)	850 lm
Luminous Intensity (Nom)	7400 cd
Color Designation	Warm White (WW)
Rated Beam Angle	15 °
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	71 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	60 Hz
Power (Rated) (Nom)	12 W

Lamp Current (Nom)	121 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.85
Voltage (Nom)	120 V

Temperature	
T-Case Maximum (Nom)	89 °C

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy star mark	Energy star
Suitable For Accent Lighting	Yes
Energy Efficiency Label (EEL)	Not applicable

Product Data	
Order product name	120V PAR30S 12W 15D 2700K 900 D AF SO
EAN/UPC - Product	046677435264
Order code	435263
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6


# PAR30/PAR20 LED

Material Nr. (12NC)	929001112204
Net Weight (Piece)	0.001 kg

## Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- Before replacing, turn off power and let lamp cool to avoid electrical shock or burn.
- CAUTION: Risk of electric shock— do not use where directly exposed to water
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005.

## Dimensional drawing



Par30S CL 120V 12W-75W 15D 2700K E26 D

Product	D	C
120V PAR30S 12W 15D 2700K 900 D AF SO	92 mm	92.7 mm

## Photometric data

