



PAR38 LED

120V PAR38 17W 25D 2700K 1200 D AF SO

Philips PAR38 LED Single Optic Lamps with AirFlux Technology improves shopping experience with superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

Product data

General Information		Lamp Current (Nom)	
Cap-Base	E26 [Single Contact Medium Screw]		167 mA
Nominal Lifetime (Nom)	25000 h	Wattage Equivalent	120 W
Switching Cycle	50000X	Starting Time (Nom)	0.5 s
Technical Type	17-120W	Warm Up Time To 60% Light (Nom)	0.5 s
		Power Factor (Nom)	0.85
		Voltage (Nom)	120 V
Light Technical		Temperature	
Color Code	827 [CCT of 2700K]		
Beam Angle (Nom)	25 °	T-Case Maximum (Nom)	89 °C
Luminous Flux (Nom)	1200 lm		
Luminous Flux (Rated) (Nom)	1200 lm	Controls and Dimming	
Luminous Intensity (Nom)	6800 cd	Dimmable	Yes
Color Designation	Warm White (WW)		
Rated Beam Angle	25 °	Approval and Application	
Correlated Color Temperature (Nom)	2700 K	Suitable For Accent Lighting	Yes
Luminous Efficacy (rated) (Nom)	71 lm/W	Energy Efficiency Label (EEL)	Not applicable
Color Consistency	<6		
Color Rendering Index (Nom)	80	Product Data	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Order product name	120V PAR38 17W 25D 2700K 1200 D AF SO
		EAN/UPC - Product	046677435387
		Order code	929001113404
		Numerator - Quantity Per Pack	1
		Numerator - Packs per outer box	6
Operating and Electrical			
Input Frequency	60 Hz		
Power (Rated) (Nom)	17 W		


PAR38 LED

Material Nr. (12NC)	929001113404
Net Weight (Piece)	0.001 kg

Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- CAUTION: Risk of electric shock - do not use where directly exposed to water.
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005

Dimensional drawing



Par38 CL 120V 17W-120W 25D 2700K E26 D

Product	D	C
120V PAR38 17W 25D 2700K 1200 D AF SO	120.3 mm	130.5 mm

Photometric data

