



PAR38 LED

17PAR38/F35 2700 DIM AF SO

Philips PAR38 LED Single Optic Lamps with AirFlux Technology improves shopping experience with superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

Product data

General Information		Power (Rated) (Nom)	
Cap-Base	E26 [Single Contact Medium Screw]		17 W
Bulb Shape	PAR38 [PAR 4.75 inch/121mm]	Lamp Current (Nom)	167 mA
Nominal Lifetime (Nom)	25000 h	Wattage Equivalent	120 W
Switching Cycle	50000X	Starting Time (Nom)	0.5 s
Technical Type	17-120W	Warm Up Time To 60% Light (Nom)	0.5 s
		Power Factor (Nom)	0.85
		Voltage (Nom)	120 V
Light Technical		Temperature	
Color Code	827 [CCT of 2700K]	T-Case Maximum (Nom)	89 °C
Beam Angle (Nom)	35 °		
Initial lumen (Nom)	1200 lm	Controls and Dimming	
Luminous Flux (Rated) (Nom)	1200 lm	Dimmable	Yes
Luminous Intensity (Nom)	3200 cd		
Color Designation	Warm White (WW)	Approval and Application	
Rated Beam Angle	35 °	Suitable For Accent Lighting	Yes
Correlated Color Temperature (Nom)	2700 K	Energy Efficiency Label (EEL)	Not applicable
Luminous Efficacy (rated) (Nom)	71 lm/W		
Color Consistency	<6	Product Data	
Color Rendering Index (Nom)	80	Order product name	120V PAR38 17W 35D 2700K 1200 D AF SO
LLMF At End Of Nominal Lifetime (Nom)	70 %	EAN/UPC - Product	046677435417
		Order code	435412
		Numerator - Quantity Per Pack	1
Operating and Electrical			
Input Frequency	60 Hz		


PAR38 LED

Numerator - Packs per outer box	6
Material Nr. (12NC)	929001113704
Net Weight (Piece)	0.001 kg

Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- CAUTION: Risk of electric shock - do not use where directly exposed to water.
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005

Dimensional drawing



Par38 CL 120V 17W-120W 36D 2700K E26 D

Product	D	C
120V PAR38 17W 35D 2700K 1200 D AF SO	120.3 mm	130.5 mm

Photometric data

