



# PAR38 LED

## 17PAR38/F35 3000 DIM AF SO

Philips PAR38 LED Single Optic Lamps with AirFlux Technology improves shopping experience with superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

### Product data

General Information		Lamp Current (Nom)	
Cap-Base	E26 [ Single Contact Medium Screw]	Wattage Equivalent	120 W
Nominal Lifetime (Nom)	25000 h	Starting Time (Nom)	0.5 s
Switching Cycle	50000X	Warm Up Time To 60% Light (Nom)	0.5 s
Technical Type	17-120W	Power Factor (Nom)	0.85
		Voltage (Nom)	120 V
Light Technical		Temperature	
Color Code	830 [ CCT of 3000K]	T-Case Maximum (Nom)	89 °C
Beam Angle (Nom)	35 °		
Initial lumen (Nom)	1250 lm	Controls and Dimming	
Luminous Flux (Rated) (Nom)	1250 lm	Dimmable	Yes
Luminous Intensity (Nom)	3400 cd		
Color Designation	White (WH)	Approval and Application	
Rated Beam Angle	35 °	Suitable For Accent Lighting	Yes
Correlated Color Temperature (Nom)	3000 K	Energy Efficiency Label (EEL)	Not applicable
Luminous Efficacy (rated) (Nom)	74 lm/W		
Color Consistency	<6	Product Data	
Color Rendering Index (Nom)	80	Order product name	120V PAR38 17W 35D 3000K 1200 D AF SO
LLMF At End Of Nominal Lifetime (Nom)	70 %	EAN/UPC - Product	046677435424
Operating and Electrical		Order code	435420
Input Frequency	60 Hz	Numerator - Quantity Per Pack	1
Power (Rated) (Nom)	17 W	Numerator - Packs per outer box	6


# PAR38 LED

Material Nr. (12NC)	929001113804
Net Weight (Piece)	0.001 kg

## Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- CAUTION: Risk of electric shock - do not use where directly exposed to water.
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005

## Dimensional drawing



Par38 CL 120V 17W-120W 36D 3000K E26 D

Product	D	C
120V PAR38 17W 35D 3000K 1200 D AF SO	120.3 mm	130.5 mm

## Photometric data

