



PAR38 LED

32PAR38/LED/830/S15/ND SO 120V 6/1

Philips PAR38 LED Single Optic Lamps with AirFlux Technology improves shopping experience with superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

Product data

General Information		Lamp Current (Nom)	
Cap-Base	E26 [Single Contact Medium Screw]		280 mA
Nominal Lifetime (Nom)	25000 h	Wattage Equivalent	250 W
Switching Cycle	50000X	Starting Time (Nom)	0.5 s
Technical Type	32-250W	Warm Up Time To 60% Light (Nom)	0.5 s
		Power Factor (Nom)	0.85
		Voltage (Nom)	120 V
Light Technical		Temperature	
Color Code	830 [CCT of 3000K]		
Beam Angle (Nom)	15 °	T-Case Maximum (Nom)	95 °C
Initial lumen (Nom)	2800 lm		
Luminous Flux (Rated) (Nom)	2800 lm	Controls and Dimming	
Luminous Intensity (Nom)	30000 cd	Dimmable	No
Color Designation	White (WH)		
Rated Beam Angle	15 °	Approval and Application	
Correlated Color Temperature (Nom)	3000 K	Suitable For Accent Lighting	Yes
Luminous Efficacy (rated) (Nom)	88 lm/W	Energy Efficiency Label (EEL)	Not applicable
Color Consistency	<6		
Color Rendering Index (Nom)	80	Product Data	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Order product name	120V PAR38 32W 15D 3000K SO
		EAN/UPC - Product	046677460518
		Order code	460519
		Numerator - Quantity Per Pack	1
		Numerator - Packs per outer box	6
Operating and Electrical			
Input Frequency	50 to 60 Hz		
Power (Rated) (Nom)	32 W		


PAR38 LED

Material Nr. (12NC)	929001202304
Net Weight (Piece)	0.540 kg

Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- CAUTION: Risk of electric shock - do not use where directly exposed to water.
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005

Dimensional drawing



PAR38 35W-70W 2800lm 15D 3000K E26 ND

Product	D	C
120V PAR38 32W 15D 3000K SO	122 mm	133 mm

Photometric data

