



# PL-T Triple 4-Pin Base Non Amalgam

## PL-T 32W/835/4P/ALTO

Philips Non-Amalgam PL-T Compact Fluorescent lamps offer designers, specifiers, and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities.

### Product data


General Information			
Cap-Base	GX24Q-3 [ GX24q-3]	LLMF 4000 h Rated	88 %
Life To 50% Failures Preheat (Nom)	13000 h	LLMF 6000 h Rated	86 %
LSF Preheat 2000 h Rated	99 %	LLMF 8000 h Rated	83 %
LSF Preheat 4000 h Rated	98 %	LLMF 12000 h Rated	81 %
LSF Preheat 6000 h Rated	97 %	Operating and Electrical	
LSF Preheat 8000 h Rated	90 %	Power (Rated) (Nom)	32 W
Light Technical		Lamp Current (Nom)	0.320 A
Color Code	835 [ CCT of 3500K]	Temperature	
Initial lumen (Nom)	2300 lm	Design Temperature (Nom)	25 °C
Luminous Flux (Rated) (Nom)	2300 lm	Controls and Dimming	
Color Designation	White (WH)	Dimmable	Yes
Chromaticity Coordinate X (Nom)	412	Mechanical and Housing	
Chromaticity Coordinate Y (Nom)	402	Cap-Base Information	4P
Correlated Color Temperature (Nom)	3500 K	Approval and Application	
Luminous Efficacy (rated) (Min)	71.9 lm/W	Energy Efficiency Label (EEL)	A
Luminous Efficacy (rated) (Nom)	71.9 lm/W		
Color Rendering Index (Nom)	82		
LLMF 2000 h Rated	92 %		

PL-T Triple 4-Pin Base Non Amalgam

Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	29 kWh
Product Data	
Order product name	PL-T 32W/835/4P/ALTO
EAN/UPC - Product	046677433444
Order code	433441

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	927933183530
Net Weight (Piece)	70.000 g
ILCOS Code	FSM-32/35/1B-E-GX24q=3

Dimensional drawing



PL-T ALTO 32W/835/4P M

Product	D	A	B	C
PL-T 32W/835/4P/ALTO	41.0 mm	86.7 mm	123.0 mm	138.7 mm

