



PL-T Triple 4-Pin Base Non Amalgam

PL-T 32W/841/4P/ALTO

Philips Non-Amalgam PL-T Compact Fluorescent lamps offer designers, specifiers, and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities.

Product data

General Information	
Cap-Base	GX24Q-3 [GX24q-3]
Life To 50% Failures Preheat (Nom)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %
Light Technical	
Color Code	841 [CCT of 4100K]
Initial lumen (Nom)	2300 lm
Luminous Flux (Rated) (Nom)	2300 lm
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	382
Chromaticity Coordinate Y (Nom)	389
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Min)	71.9 lm/W
Luminous Efficacy (rated) (Nom)	71.9 lm/W
Color Rendering Index (Nom)	80
LLMF 2000 h Rated	92 %


LLMF 4000 h Rated	88 %
LLMF 6000 h Rated	86 %
LLMF 8000 h Rated	83 %
LLMF 12000 h Rated	81 %
Operating and Electrical	
Power (Rated) (Nom)	32 W
Lamp Current (Nom)	0.320 A
Temperature	
Design Temperature (Nom)	25 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	4P
Approval and Application	
Energy Efficiency Label (EEL)	A

PL-T Triple 4-Pin Base Non Amalgam

Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	29 kWh
Product Data	
Order product name	PL-T 32W/841/4P/ALTO
EAN/UPC - Product	046677433451
Order code	433458

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	927933184130
Net Weight (Piece)	70.000 g
ILCOS Code	FSM-32/41/1B-E-GX24q=3

Dimensional drawing



PL-T ALTO 32W/841/4P M

Product	D	A	B	C
PL-T 32W/841/4P/ALTO	41.0 mm	86.7 mm	123.0 mm	138.7 mm

