



Accessories for InteGrade LED fixtures

LED Power Driver 80W 24V

InteGrade LED accessories enable easy creation of shelf or display lighting based on InteGrade LED fixtures. These accessories include a choice of power cables, Xitanium Constant Voltage Outdoor LED power drivers and, where necessary, mounting clips. With this choice of accessories your shelf or display lighting will always be a perfect fit. The InteGrade LED fixture comprises a profile, one or more connectors, and inline locks. These parts can be ordered as spare parts if required.

Product data

Operating and Electrical

Input Frequency	50 to 60 Hz
Total Harmonic Distortion IEC (Max)	20 %
Maximum Efficiency	80 %
Power Factor 100% Load (Min)	0.9
Output Current (Nom)	3300 mA
Input Voltage (AC)	100-240 V
Output Voltage Tolerance (Max)	5 %
Output Voltage Tolerance (Min)	-5 %
Input Power (Nom)	96 W
Inrush Current Peak (Max)	130 A
Output Voltage	24.3 V
Inrush Current Width To 50% Of Peak	200 μ s

Wiring

Connector Type Input Terminals	Wago 250
Output Wire Length	300 mm

Output Wire Cross Section (Nom)	0.82 mm ²
Input Wire Cross Section (Nom)	0.82 mm ²

Temperature

T-Ambient (Max)	60 °C
T-Ambient (Min)	-30 °C
T-Storage (Max)	85 °C
T-Storage (Min)	-40 °C
T-Case Lifetime (Nom)	70 °C
T-Case Maximum (Max)	85 °C

Controls and Dimming

Control Interface	None
-------------------	------

Mechanical and Housing


Housing Color	White
---------------	-------

Accessories for InteGrade LED fixtures

Approval and Application	
Isolation Classification	Class II
Approval Marks	CE marking
Product Data	
Full product code	871829121526400
Order product name	LED Power Driver 80W 24V
EAN/UPC - Product	8718291215264

Order code	929000653906
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929000653906
Net Weight (Piece)	0.620 kg

Dimensional drawing



LED Power Driver 80W 24V

Product	D1	A2	B2	C1	A1	B1
---------	----	----	----	----	----	----

