



Representative

Catalog Number: CH610EH075MV
Product ID: 7TAA080090R0002
UPC Number: 78620998786
Status: Active

Double lever locking inline coupler hood with top entry, 10 contacts, NPT entry - 1 Inch x 3/4 Inch

North American Specifications (UNSPSC)

UNSPSC	39121424 Terminal block covers
IGCC	4594 Terminal block covers
Brand Name	Pos-E-Kon
Type	Coupler Hoods
Application	For inline, portable or special service connections
Standard	UL E215386
Material	Die-Cast Aluminum Alloy
Finish	Epoxy Powder Coated
Temperature Rating	-40 Degrees F to +257 Degrees F

European Specifications (ETIM)

ETIM	EC000437 Housing for industrial connectors
Shape	Rectangular
Length	72.9996mm
Height	77.47mm
Width	43.0022mm
Type of housing	Coupling housing
Position cable feed	Sideways
With cable screw gland	N
With hinged lid	N
Material housing	Aluminium
Coating housing	With powder coating
Locking mechanism	Double locking levers
Inflammability class of insulation material acc. with UL94	V0
Operation temperature	-40 - +125°C

Packaging

Outer Quantity	10
Outer Dimensions (inches)	4x4x6
Weight Uom	55.5 lbs. per 100

Documents / Support Tools

Technical Data Sheet CA	Available on Website
-------------------------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com