

Precision Plumbing Products "Specify with Confidence - Install with Pride"

LEAD FREE

WATER HAMMER ARRESTORS STAINLESS STEEL #316 THREADED

www.pppinc.net

Adaptable to your individual needs:

PPP Stainless Steel Hammer Arrestors are available for all types of fluid systems - water, deionized and triple distilled water, chemicals and petroleum products.

Finished to your Specifications:

When ordering, the expected mean spike pressure must be specified as well as the chemical make-upof the fluid in the system and the maximum temperature. Arrestors may be charged at the factory with either air or dry nitrogen per your specification.

If arrestors are to be used in systems pumping volatile fluids it is mandatory that they be charged with dry nitrogen.

Arrestor Construction:

Stainless Steel Adapter, Cap, Piston, and Barrel with high pressure "O"rings. All stainless steel parts are fabricated from 316 materials.

Application:

Chemicals. Corrosive fluids or environment. distilled and triple distilled water, or fluids under high pressure.

Available in NPT or BSP threads.

Normal operating pressure for threaded arrestors 35 to 500 PSIG. Spike pressure not to exceed 2,000 PSIG. No access panel required. Consult Local Code.

PROJECT SUBMITTAL	(百里)
Project:	— A ·
Contractor:	
Engineer:	
Date Submitted:	



THREADED ARRESTORS

PART NUMBER	A NPT	B OAL	NITROGEN PRELOAD PSI
SS-500-316	1/2"	5 1/4"	60
SS-750-316	3/4"	6 1/2"	60
SS-1000-316	1"	6 15/16"	60
SS-1250-316	1"	8 9/16"	60
SS-1500-316	1"	10 9/16"	60
SS-2000-316	1"	11 3/16"	60

For further information:

Contact your local PPP representative, or contact the factory directly. We will help you to determine your individual needs and give you a quotation at no obligation.

U.S. Patent No.3,633,62



Prepared By:__

Precision Plumbing Products

Division of JL Industries, Inc. 802 SE 199th Avenue Portland, Oregon 97233 T (503) 256-4010 F (503) 253-8165

www.pppinc.net











