





US ANSI 209.1 CSA 294.1-05

Non-vented meet ANSI Z89.1-2009 Standards, Type I, Class C, G, and E; Vented meet ANSI Z89.1-2009 Standards, Type I, Class C and G



4-Point	4-Point	4-Point	6 -Point	6-Point	
Standard Ratchet	Vented Ratchet	Standard Glide Lock	Standard Ratchet	Standard Glide Lock	
Part	Part	Part	Part	Part	Color
HP44110••	HP44110V•	HP44010•	HP46110•	HP46010•	White
HP44112••	HP44112V•	HP44012•	—	HP46012•	Gray
HP44113••	—	—	—	—	Slate Gray
HP44117••					Graphite
HP44120••	HP44120V•	HP44020•	HP46120•	HP46020•	Red
HP44130••	HP44130V•	HP44030•	HP46130•	HP46030•	Yellow
HP44131••	HP44131V•	—	HP46131•	—	Hi-Vis* Lime
HP44135••	—	HP44035•	HP46135•	HP46035•	Green
HP44141••	HP44141V•	HP44041•	HP46141•	HP46041•	Hi-Vis* Orange
HP44160••	HP44160V•	HP44060•	HP46160•	HP46060•	Blue
HP44162••	—	_	_	_	Light Blue

\*Hi-Vis colors have been tested for the "HV" mark.

## **RIDGELINE R**

- Low profile design Offers a low center of gravity for better balance.
- ABS material Strong, yet ultra-light for seemingly weightless protection.
- Replaceable sweat band Padded fabric and polyurethane foam for all day wear.
- Rear padded suspension Provides additional level of comfort on the wearers' neck.
- Vented pressure pad Keeps the straps in place providing an additional level of comfort.
- Swinging hinge points Allows you to find the most comfortable position on the back of your head.
- Top and rear ventilation holes (Vented options only)- Keeps your head cool and dry for all day wear.

## GENERAL SPECIFICATION

General Dimensions: 28cm x 21.5cm x 16cm

Shell Thickness: 2-4.5mm

## Weight: 347g

## PACKAGING

Case: 16 pcs

COMPONENT	MATERIAL	FEATURES	
Shell	High Impact ABS	Lightweight and durable	
Suspension	High Density PE	Adjustable with swing and ratchet. Replaceable sweat band. Easy to install and	
	High Impact Nylon	adjust to accommodate different head sizes.	
Sweat Band	Fabric and PU Foam	N/A	