

PROVOQ®

SUPERIOR COMFORT AND FIT



PART

SB7210S**

SB7210ST**

SB7220S**

SB7220ST**

SB7230S**

SB7275S**

SB7280S**

LENS

- Clear
- Clear (Anti-Fog)
- Gray
- Gray (Anti-Fog)
- Amber
- Blue Mirror
- Indoor/Outdoor Mirror

- Superior comfort and fit.
- Soft nose piece provides comfort fit.
- Rubber temples provides non-slip comfort.
- Offer 99.9% protection against harmful UV rays.
- Lenses are coated for superior scratch resistance.
- Economical lightweight glasses offer superior protection.








GENERAL SPECIFICATION
Bridge: 16.66mm
Closest Point Between Lens: 8.18mm
Closest Point Between Strap Holding Parts: 79.35mm
Lens Base: 9 curve
Lens Size Diagonal: 79.83mm
Lens Size Vertical: 41.12mm
Lens Thickness: 2.4mm
Overall Length (Lens-Tip): 158mm
Overall Width: 136mm
PD: 64mm
Weight: 24.9g

PROVOQ®

SUPERIOR COMFORT AND FIT

PACKAGING
Polybag: 1 pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9 base curve
Frame	N/A	N/A
Nose Piece	TPR	N/A
Sleeve (on temple)	TPR	Integral to temple
Temple	Polycarbonate	Streamlined design
Hinge	Polycarbonate	Integral to temple
Screw	Plated steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB7210S	 Clear	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7210ST	 Clear (Anti-Fog)	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7220S	 Gray	P Z87 + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7220ST	 Gray (Anti-Fog)	P Z87 + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7230S	 Amber	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7275S	 Blue Mirror	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7280S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices