



PYRAMEX
Perform At Your Peak

PMXTREME® ANSI CE



RUBBER NOSEPIECE



INCLUDES STRAP



RUBBER TIPS

Built-in rubber nosepiece

Ventilated flexible temples with rubber temple tips

Includes black lanyard cord

Part No.	Black Frame with Cord
SB6310SP •	Clear
SB6310STP ••	AF Clear
SB6320SP •	Gray
SB6320STP ••	AF Gray
SB6330SP •	Amber
SB6345SP •	Ice Orange Mirror
SB6360SP •	Infinity Blue
SB6370SP •	Silver Mirror
SB6375SP •	Blue Mirror
SB6376SP •	Smoke Green Mirror
SB6380SP •	I/O Mirror
Part No.	Camo Frame with Cord
SCM6310STP •	AF Clear
SCM6318STP •	AF Sandstone Bronze
SCM6320STP •	AF Gray
Part No.	Red Frame with Cord
SR6320SP •	Gray



PMXTREME Rx ANSI



RUBBER NOSEPIECE



RUBBER TIPS

Includes RX insert which accommodates -3.0 to +3.0 prescription lenses

Take insert to local optometrist for Rx lens installation

Part No.	Black Frame
SB6310STRX •	AF Clear
SB6320STRX •	AF Gray



There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards [•] and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] [••] standards.



PYRAMEX
Perform At Your Peak

PMXTREME® LED **ANSI CE**



RUBBER NOSEPIECE



RUBBER TIPS

Super bright swiveling LED bulbs (three lumens per side) allows you to see in dark places while keeping your hands free

Built-in rubber nosepiece and rubber temples tips

The alkaline batteries provide up to 50 hours of use before replacing. Three L44 alkaline batteries per temples (six total) are included

Easy to use push button on/off switches are located at the top of each temple

Part No.	Black Frame
SB6310STPLED ●●	AF Clear



PMXTREME Readers **ANSI**



RUBBER NOSEPIECE



INCLUDES STRAP



RUBBER TIPS

Part No.	Black Frame with Cord
SB6310SPR15 ●	Clear +1.5 Mag
SB6310SPR20 ●	Clear +2.0 Mag
SB6310SPR25 ●	Clear +2.5 Mag

PMXTREME LED Readers **ANSI**



RUBBER NOSEPIECE



RUBBER TIPS

Part No.	Black Frame
SB6310STPLEDR15 ●	AF Clear +1.5 Mag
SB6310STPLEDR20 ●	AF Clear +2.0 Mag
SB6310STPLEDR25 ●	AF Clear +2.5 Mag

There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards [●] and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] [●] standards.

PMXTREME®

General Specifications

Weight: 27 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Temple tips: rubber

Part No.	Lens Marking	Temple Marking
SB6310SP	P + U6	P Z87 +
SB6310STP	P + U6	P Z87 +
SB6320SP	P + U6 L3	P Z87 +
SB6320STP	P + U6 L3	P Z87 +
SB6330SP	P + U6	P Z87 +
SB6345SP	P + L3	P Z87 +
SB6360SP	P + U6 L1.3	P Z87 +
SB6370SP	P + L3	P Z87 +
SB6375SP	P + L3	P Z87 +
SB6376SP	P + L3	P Z87 +
SB6380SP	P + U6 L1.7	P Z87 +
SCM6310STP	P + U6	P Z87 +
SCM6318STP	P + U6 L2.5	P Z87 +
SCM6320STP	P + U6 L3	P Z87 +
SR6320SP	P + U6 L3	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light
 L3: 18% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

PMXTREME Rx

General Specifications

Weight: 29 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 146 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Temple tips: rubber
 Rx Insert: thermoplastic (TR90)

Part No.	Lens Marking	Temple Marking
SB6310STRX	P + U6	P Z87 +
SB6320STRX	P + U6 L3	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L3: 18% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

PMXTREME LED

General Specifications

Weight: 50 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Temple tips: rubber

Part No.	Lens Marking	Temple Marking
SB6310STPLED	P + U6	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact



PMXTREME® Readers

General Specifications

Weight: 27 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Temple tips: rubber

Part No.	Lens Marking	Frame Marking	Temple Marking
SB6310SPR15	P Z87 + U6	+ 1.50	P Z87 - 2+
SB6310SPR20	P Z87 + U6	+ 2.00	P Z87 - 2+
SB6310SPR25	P Z87 + U6	+ 2.50	P Z87 - 2+

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact

Frame Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5

PMXTREME LED Readers

General Specifications

Weight: 50 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Temple tips: rubber

Part No.	Lens Marking	Frame Marking	Temple Marking
SB6310STPLEDR15	P Z87 + U6	+ 1.50	P Z87 - 2+
SB6310STPLEDR20	P Z87 + U6	+ 2.00	P Z87 - 2+
SB6310STPLEDR25	P Z87 + U6	+ 2.50	P Z87 - 2+

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact

Frame Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5