# **PMXTREME®**



OPTIMAL STYLE IN SAFETY EYEWEAR



PART SB6310SP*	LENS Clear	PART SB6370SP*	LENS Silver Mirror
SB6310STP*	Clear (Anti-Fog)	SB6375SP*	Blue Mirror
SB6320SP*	Gray	SB6380SP*	Indoor/Outdoor Mirror
SB6320STP*	Gray (Anti-Fog)	SCM6310STP*	Clear
SB6330SP*	Amber	SCM6318STP*	Sandstone Bronze
SB6345SP*	Ice Orange Mirror	SCM6320STP*	Gray
SB6360SP*	Infinity Blue	SR6320SP*	Gray

- Built-in rubber nose piece provides all day comfort.
- Includes black lanyard cord for extra security while wearing.
- · Rubber temple tips keep eyewear secure for the active worker.
- Extreme style in safety eyewear, with clean lines and sports appeal.
- Ventilated, straight-back flexible temples provide cool, pressure-free fit.
- Scratch resistant polycarbonate lenses provide maximum vision protection, filter out 99% of harmful UV rays.

GENERAL SPECIFICATION		
Bridge: 14mm		
Lens Base: 9 Curve		
Lens Size Diagonal: 78mm		
Lens Size Vertical: 46mm		
Lens Thickness: 2.2mm		
Overall Length (Lens-Tip): 103mm		
Overall Width (Hinge-Hinge): 140mm		
PD: 72mm		
Weight: 27gm		

PACKAGING				
Polybag: 1pc				
Inner Box: 12 pcs				
Case: 300 pcs				

# **PMXTREME®**

## OPTIMAL STYLE IN SAFETY EYEWEAR

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9 base curve, molded lens attached to the frame
Frame	Nylon	Half Frame
Nose Piece	Rubber	N/A
Sleeve (on temples)	Hard Rubber	N/A
Temple	Nylon	N/A
Hinge Screw	Nickel Silver	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB6310SP	Clear	P + U6	P Z87 +
SB6310STP	Clear (Anti-Fog)	P + U6	P Z87 +
SB6320SP	Gray	P + U6 L3	P Z87 +
SB6320STP	Gray (Anti-Fog)	P + U6 L3	P Z87 +
SB6330SP	Amber	P + U6	P Z87 +
SB6345SP	Ice Orange Mirror	P+L3	P Z87 +
SB6360SP	Infinity Blue	P + U6 L1.3	P Z87 +
SB6370SP	Silver Mirror	P + U6 L1.3	P Z87 +
SB6375SP	Blue Mirror	P + U6 L1.3	P Z87 +
SB6380SP	Indoor/Outdoor Mirror	P + U6 L1.7	P Z87 +
SCM6310STP	Clear	P + U6	P Z87 +
SCM6318STP	Sandstone Bronze	P + U6 L2.5	P Z87 +
SCM6320STP	Gray	P+U6L3	P Z87 +
SR6320SP	Gray	P+U6L3	P Z87 +

### **LENS MARKING**

#### Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

#### **UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

#### **Visible Light Filters:**

L1.3: 85% Max. Visible Light L1.7: 55% Max. Visible Light L2.5: 29% Max. Visible Light L3: 18% Max. Visible Light

### FRAME MARKING

#### Symbols:

P: Manufacturer's mark

**Z87:** ANSI standard for Eye and Face protection devices

+: High Impact