

PMXSLIM®

Slim Fit for Smaller Facial Features



Black Temples

Part	Lens
SB7110S●●	Clear
SB7110ST●●●●	Clear H2X Anti-Fog
SB7120S●●	Gray
SB7120ST●●●●	Gray H2X Anti-Fog
SB7138S●●●	Sandstone Bronze
SB7180S●●●	Indoor/Outdoor Mirror

- PMXSLIM has a slim fit for smaller facial features.
- Lenses provide 99.9% protection against harmful UV rays.
- Dual injected temple design includes soft rubber tips for a non-slip fit.
- Soft, adjustable PVC nose piece generates a cushion for all day comfort.
- High quality optics provide a clear, panoramic view without obstruction.
- Wrap-around, single lens design performs with incredible 10 base curve, including side protection that extends to the temples.

GENERAL SPECIFICATION

Bridge: 14.5mm
Closest Point Between Lens: 9mm
Closest Point Between Temple Tips: 86mm
Lens Base: 10 Curve
Lens Size Diagonal: 137.7mm
Lens Size Vertical: 45mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 170mm
Overall Width (Hinge-Hinge): 129mm
PD: 68mm
Weight: 25g

PACKAGING

Polybag: 1pc







Inner Box: 12 pcs

Case: 300 pcs

PMXSLIM[®]

Slim Fit for Smaller Facial Features

COMPONENT	MATERIAL	FEATURES
Hinge	Polycarbonate	3 barrel type, integral to lens/temples
Lens	Polycarbonate	10 base curve, wrap around design with side protection extended to temples
Temple Tips	Polycarbonate TPE	Spatula with soft tip end
Side Shields	Polycarbonate	Integral to Lens
Nose Piece	PVC	Slip on type, pillow softness
Screw	Stainless Steel	Standard hinge screw
Frame	Polycarbonate	Integral to Lens

PART	LENS	LENS MARKING	FRAME MARKING
SB7110S	 Clear	P Z87 + U6	P Z87 +
SB7110ST	 Clear H2X Anti-Fog	P Z87 + U6	P Z87 +
SB7120S	 Gray	P Z87 + U6 L2.5	P Z87 +
SB7120ST	 Gray H2X Anti-Fog	P Z87 + U6 L2.5	P Z87 +
SB7138S	 Sandstone Bronze	P Z87 + S	P Z87 +
SB7180S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact