

EVER-LITE®

Lightweight Spectacle – 22 gm

**Black Frame****Part**

SB8610D•••

 Clear

SB8610DT•••

 Clear H2X Anti-Fog

SB8610DTM•••

 Clear H2MAX Anti-Fog

SB8620D•••

 Gray

SB8620DT•••

 Gray H2X Anti-Fog

SB8620DTM•••

 Gray H2MAX Anti-Fog

SB8623D•••

 Dark Gray

SB8623DT•••

 Dark Gray H2X Anti-Fog
Part

SB8624D•••

 Photochromatic

SB8630D•••

 Amber

SB8660D•••

 Infinity Blue

SB8660DT•••

 Infinity Blue H2X Anti-Fog

SB8665D•••

 Ice Blue Mirror

SB8680D•••

 Indoor/Outdoor Mirror

SB8680DT•••

 Indoor/Outdoor Mirror Anti-Fog

- Soft nosepiece for snug fit.
- Semi-frame & slim co-material temple design for lightweight spectacle – 22 gm.
- Offers a clear panoramic view without obstruction.
- 8 base wraparound lens provides full front side protection.
- Scratch-resistant, polycarbonate lens provide 99.9% of UV protection.
- H2MAX creates a high performing, superior anti-fog coating that is durable enough to withstand repeated cleaning without losing adhesion. H2MAX ensures maximum clarity in the most extreme temperature and humidity conditions, and it also adds a layer to the lens that is abrasion, chemical, and UV-resistant.

GENERAL SPECIFICATION

Bridge: 11.2mm

Closest Point Between Lens: 11mm

Closest Point Between Temple Tips: 70mm

Lens Base: 8 Curve

Lens Size Diagonal: 79.6mm

Lens Size Vertical: 43.3mm

Lens Thickness: 1.8mm

Overall Length (Lens-Tip): 163.5mm

Overall Width (Hinge-Hinge): 134.3mm

PD: 64mm

Weight: 22gm

PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs
















Photochromatic

Sold individually

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve
Frame	Polycarbonate	Lens clipped on frame
Nose piece	TPR	Universal fit
Temple	Polycarbonate/TPE	Co-injected temple to avoid slipping
Hinge	Polycarbonate	3 barrel type
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB8610D	 Clear	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8610DT	 Clear H2X Anti-Fog	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8610DTM	 Clear H2MAX Anti-Fog	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8620D	 Gray	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8620DT	 Gray H2X Anti-Fog	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8620DTM	 Gray H2MAX Anti-Fog	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8623D	 Dark Gray	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8623DT	 Dark Gray H2X Anti-Fog	P + S	P Z87 +
SB8624D	 Photochromatic	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8630D	 Amber	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8660D	 Infinity Blue	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8660DT	 Infinity Blue H2X Anti-Fog	P + S	P Z87 +
SB8665D	 Ice Blue Mirror	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8680D	 Indoor/Outdoor Mirror	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8680DT	 Indoor/Outdoor Mirror Anti-Fog	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 P c SEI CAN/CSA Z94.3-07: CAN/CSA standard for protection devices