

ACCURIST®

Sporty design for on & off the job



Black Frame

Part

Lens

SB8710DTP••	Clear Anti-Fog
SB8715DTP••	Coffee Anti-Fog
SB8720DTP••	Gray Anti-Fog
SB8725DTP••	Light Gray Anti-Fog
SB8770DP••	Silver Mirror
SB8775DP••	Blue Mirror

Black and Red Frame

Part

Lens

SBR8710DTP••	Clear Anti-Fog
SBR8720DTP••	Gray Anti-Fog
SBR8770DP••	Silver Mirror

- Built-in rubber nosepiece.
- Sporty design for on and off the job.
- Anti-fog lenses provide 99.9% protection against harmful UV rays.
- Inner foam padding is flame resistant and provides excellent protection from wind, dust and other debris.
- Durable frame features dual-injected straightback temples for comfortable and secure fit against your head.

GENERAL SPECIFICATION

Bridge: 16mm

Closest Point Between Lens: 16mm

Closest Point Between Temples Tips: 95mm

Lens Base: 10 Curve

Lens Size Diagonal: 62mm

Lens Size Vertical: 35mm

Lens Thickness: 2mm

Overall Length [Lens-Tip]: 116mm

Overall Width [Hinge-Hinge]: 136mm

PD: 64mm

Weight: 29gm










PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Carton: 300 pcs

COMPONENT	MATERIAL	FEATURES
Temple	Polycarbonate/Rubber	Spatula with double injection rubber
Frame	Nylon	Dual lens frame with side protection
Lens	Polycarbonate	Full eye protection 10 curve lens
Foam	RB	Fire retardant
Hinge	Polycarbonate	Integral to frame/temple
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB8710DTP	 Clear Anti-Fog	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8715DTP	 Coffee Anti-Fog	P + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8720DTP	 Gray Anti-Fog	P + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8725DTP	 Light Gray Anti-Fog	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8770DP	 Silver Mirror	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8775DP	 Blue Mirror	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SBR8710DTP	 Clear Anti-Fog	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SBR8720DTP	 Gray Anti-Fog	P + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SBR8770DP	 Silver Mirror	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices