



Representative

**Catalog Number:** 4464SC  
**Product ID:** 7TAA057570R0012  
**UPC Number:** 70891714157  
**Status:** Active

Delayed Reaction Angled Surface Mount Receptacle, 20 Amp, 2 Pole 3 Wire, XP Screw Cap

### North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	Russellstoll Hazardous-Duty Plugs, Receptacles and Interlocks
Special Features	Circuit-breaking receptacles, plugs and connectors ensure complete circuit breaking under full rated loads. Equipment grounding is provided by means of a separate pole that makes contact before and breaks contact after the circuit poles. The delayed action operation sequence is as follows: Insert plug, turn left push in to make electrical contact then turn right to prevent accidental disconnection. To withdraw plug, the reverse procedure is followed, which provides time for extinction of the arc and cooling before the plug can be completely withdrawn.
Application	For use in hazardous materials environment like: Gas or Vapor, Dust, or Fibers/Flyings
Number Of Poles	2
Number Of Wires	3
Amperage Rating	20 Amp
Material	Cast Aluminum

### European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	20A
Number of poles	2

### Packaging

Outer Quantity	1
Weight Uom	3.75 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)