



# Russellstoll

## DuraGard Waterproof Connections

T&B Catalog Number:

9P34U0

UPC Number:

70891717359

Status:

Active

Description:

DuraGard Male Plug, 30 Amp, 3 Pole 4 Wire, 600VAC/250VDC

### Features

Not just "watertight"; Waterproof for washdown duty (DurORing Sealing) that eliminates the need for costly "weather boots" or "adapters."

Durable, tough and flame safety rated housings for superior performance in corrosive environments.

Safe and reliable power connections: Pin and Sleeve, Voltage Polarized for more power operating cooler and ground pin keyed for voltage polarization (O-ring sealed).

Easy to wire with "drop-in" rear-loaded interiors using no assembly screws versus 3-5 or more with other connectors.

### Application

For use where electrical connections need protection from water and/or dust entrance to the contacts or the wiring compartment.

For use with any application where electrical connections need protection from water and/or dust entrance to the contacts or the wiring compartment

For washdown and light marine applications: watertight/waterproof such as food processing plants, bottling and beverage plants, pulp and paper factories, pharmaceutical manufacturing, barge and workboat applications, and outdoor construction sites.

For use with computer systems: data center and OEM products such as, raised floor applications, main power connections and critical power for test, instrumentation, telephone and medical equipment.

### General

|            |   |
|------------|---|
| Style      | Male Plug                                   |
| Material   | DuraV high impact body and collars          |
| Material_1 | CDA 360 solid brass pin and sleeve contacts |
| Material_2 | Thermoset interiors                         |
| Frequency  | 60 Hz                                       |
| Amperage   | 30 Amp                                      |
| Pole/Wire  | 3P/4W                                       |
| System     | Washdown Industrial & Light Marine          |

### Dimension Information

|                    |                      |
|--------------------|----------------------|
| Overall Dimensions | Available on Website |
|--------------------|----------------------|

### Specifications

|         |                       |
|---------|-----------------------|
| Voltage | Through 600VAC/250VDC |
|---------|-----------------------|

|                            |                      |
|----------------------------|----------------------|
| Engineering Specifications | Available on Website |
|----------------------------|----------------------|

### **Packaging**

|                    |                 |
|--------------------|-----------------|
| Package in Units   | 50              |
| T&B Sold in UOM    | Each            |
| T&B Weight Per UOM | 69 lbs. per 100 |

### **Application Support**

|                                |                      |
|--------------------------------|----------------------|
| Overview                       | Available on Website |
| Russellstoll Application Guide | Available on Website |

### **Certifications**

|                 |     |
|-----------------|-----|
| RoHS Compliance | Yes |
| USCG Approved   | Y   |

### **Certifications**



File Nbr:  
E2630

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com