



Actual

**Catalog Number:** DBRE6521060K0  
**Product ID:** 7TAA057070R0044  
**UPC Number:** 70891726199  
**Status:** A

MaxGard Interlocked Receptacle, Explosion Proof with Control Contacts, 60 Amp, 4 Pole 5 Wire, 30Y 250/440V, 60Hz

### North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	Explosion-proof waterproof circuit breaker interlocked receptacle O-ring sealed along with optional control contacts fully UL listed.
Application	For use with watertight plugs and inlets where portable equipment is on stand by and plugs are not in use.
Number Of Poles	4
Number Of Wires	5
Amperage Rating	60 Amp
Voltage Rating	440V
Material	Cast Aluminum

### European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	60A
Number of poles	4

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	20x9x14
Weight Uom	45 lbs. Each

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)