



Actual

**Catalog Number:** DBRF440440000  
**Product ID:** 7TAA057980R0451  
**UPC Number:** 70891714905  
**Status:** Active

MaxGard Interlocked Receptacle with Circuit Breaker, 400 Amp, 3 Pole 4 Wire, 30 480V, 60Hz, Breaker Trip Rating 400 Amp

### UNSPSC Specifications

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	For use with watertight plugs and inlets where portable equipment is on stand by and plugs are not in use.
Material	Cast Aluminum

### ETIM Specifications

ETIM	EC001322 Round socket/plug for high currents
Amperage	400A
Number of poles	3

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	32x18x14
Weight Uom	115 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)