



Actual

Catalog Number: DBRS1404100/901238
Product ID: 7TAA057070R0139
UPC Number: 70891733176
Status: Active

MaxGard Interlocked Receptacle with Circuit Breaker, 100 Amp, 3 Pole 4 Wire, 30 480V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	For use with watertight plugs and inlets where portable equipment is on stand by and plugs are not in use.
Number Of Poles	3
Number Of Wires	4
Amperage Rating	100 Amp
Voltage Rating	480V
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	100A
Number of poles	3

Packaging

Outer Quantity	1
Outer Dimensions (inches)	24x13x11.13
Weight Uom	32 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com