



Actual

**Catalog Number:** DBRS141610000  
**Product ID:** 7TAA057070R0142  
**UPC Number:** 70891719826  
**Status:** A

MaxGuard Interlocked Receptacle with Circuit Breaker, 100 Amp, 3 Pole 4 Wire, 30 208V, 60Hz, Breaker Trip Rating 100 Amp

### North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGuard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	For use with watertight plugs and inlets where portable equipment is on stand by and plugs are not in use.
Number Of Poles	3
Number Of Wires	4
Amperage Rating	100 Amp
Voltage Rating	208V
Material	Cast Aluminum

### European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	100A
Number of poles	3

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	24x13x11
Weight Uom	32 lbs. Each

### For further technical assistance, please contact us...

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)