Thomas&Betts



Representative

Catalog Number: Product ID: UPC Number: Status:

DF3504FRABK 7TAA057030R0220

70891719083 Active

MaxGard Female Flap Cap Receptacle with Angle Adapter, Junction Box and Control Contacts, 30 Amp, 4 Pole 5 Wire, 30Y 277/480V, 60Hz

UNSPSC Specifications	
UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Туре	MaxGard Interconnection Systems
Special Features	Waterproof construction provides environmen- tal separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	For use in "People Movers" which re- quire aire conditioning and heater unit power when docked at end of line locations for maintenance and overhaul, ex: Dulles Airport.
Material	Cast Aluminum
ETIM Specifications	

ETIM Specifications

ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Construction type	Wall socket
Number of poles	4

Packaging

Outer Quantity1Weight Uom5.7 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com