



Representative

Catalog Number: DF3516FR000
Product ID: 7TAA057980R0552
UPC Number: 70891718293
Status: Active

MaxGard Female Flap Cap Receptacle, 30 Amp, 4 Pole 5 Wire, 30Y 120/208V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121406 Electrical receptacles
IGCC	4536 Electrical receptacles
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	For use in "People Movers" which require air conditioning and heater unit power when docked at end of line locations for maintenance and overhaul, ex: Dulles Airport.
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Construction type	Wall socket
Number of poles	4

Packaging

Outer Quantity	1
Weight Uom	3.5 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com