



Actual

Catalog Number: DFRF15160
Product ID: 7TAA057070R0219
UPC Number: 70891731330
Status: Active

MaxGard Fused Male Plug Disconnect Interlocked Receptacle (Nema 12/3R), 100 Amp, 4 Pole 5 Wire, 30Y 120/208V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	There are three external lockout points, a door safety switch and a clear shield for test probes.
Application	For use with watertight plugs and inlets where portable equipment is on stand by and plugs are not in use.
Number Of Poles	4
Number Of Wires	5
Amperage Rating	100 Amp
Voltage Rating	208V
Material	Steel

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	100A
Number of poles	4

Packaging

Outer Quantity	1
Outer Dimensions (inches)	33x18x10.5
Weight Uom	25 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com