



Actual

Catalog Number: DFRF31070
Product ID: 7TAA057070R0220
UPC Number: 70891731463
Status: A

MaxGard Fused Male Plug Disconnect Interlocked Receptacle (Nema 12/3R), 30 Amp, 2 Pole 3 Wire, 125V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121406 Electrical receptacles
IGCC	4536 Electrical receptacles
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	There are three external lockout points, a door safety switch and a clear shield for test probes.
Application	For use with watertight plugs and inlets where portable equipment is on stand by and plugs are not in use.
Material	Heavy .060 steel galvaneel with baked enamel, NE-MA 3R/12 Construction

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Number of poles	2

Packaging

Outer Quantity	1
Outer Dimensions (inches)	33x18x10.5
Weight Uom	8 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com