



Actual

Catalog Number: DFRF34040
Product ID: 7TAA057070R0221
UPC Number: 70891717056
Status: Active

MaxGard Fused Male Plug Disconnect Interlocked Receptacle (Nema 12/3R), 30 Amp, 3 Pole 4 Wire, 30 480V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121406 Electrical receptacles
IGCC	4536 Electrical receptacles
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	There are three external lockout points, a door safety switch and a clear shield for test probes.
Application	For use with watertight plugs and inlets where portable equipment is on stand by and plugs are not in use.
Material	Heavy .060 steel galvaneel with baked enamel, NE-MA 3R/12 Construction

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Number of poles	3

Packaging

Outer Quantity	1
Outer Dimensions (inches)	26.25x15.38x15.69
Weight Uom	34.4 lbs. Each

Documents / Support Tools

Technical Data Sheet CA	Available on Website
-------------------------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com