



Actual

**Catalog Number:** DFRF34140  
**Product ID:** 7TAA057070R0223  
**UPC Number:** 70891718873  
**Status:** A

MaxGard Fused Male Plug Disconnect Interlocked Receptacle (Nema 12/3R), 30 Amp, 3 Pole 4 Wire, 30 600V, 60Hz

### North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	There are three external lockout points, a door safety switch and a clear shield for test probes.
Application	For use with watertight plugs and inlets where portable equipment is on stand by and plugs are not in use.
Number Of Poles	3
Number Of Wires	4
Amperage Rating	30 Amp
Voltage Rating	600V
Material	Steel

### European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Number of poles	3

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	26.25x15.38x15.69
Weight Uom	8 lbs. Each

### For further technical assistance, please contact us...

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)