



Actual

Catalog Number: DFRF65160
Product ID: 7TAA057070R0229
UPC Number: 70891731434
Status: Active

MaxGard Fused Male Plug Disconnect Interlocked Receptacle (Nema 12/3R), 60 Amp, 4 Pole 5 Wire, 30Y 120/208V, 60Hz

North American Specifications (UNSPSC)

| | |
|------------------|--|
| UNSPSC | 39121404 Electrical sleeves |
| IGCC | 4528 Electrical sleeves |
| Brand Name | Russellstoll |
| Type | MaxGard Interconnection Systems |
| Special Features | There are three external lockout points, a door safety switch and a clear shield for test probes. |
| Application | For use with watertight plugs and inlets where portable equipment is on stand by and plugs are not in use. |
| Number Of Poles | 4 |
| Number Of Wires | 5 |
| Amperage Rating | 60 Amp |
| Voltage Rating | 208V |
| Material | Steel |

European Specifications (ETIM)

| | |
|-----------------|--|
| ETIM | EC001322 Round socket/plug for high currents |
| Amperage | 60A |
| Number of poles | 4 |

Packaging

| | |
|---------------------------|--------------|
| Outer Quantity | 1 |
| Outer Dimensions (inches) | 33x18x10.5 |
| Weight Uom | 27 lbs. Each |

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com