

# Russellstoll

## MaxGard Interconnection Systems

### T&B Catalog Number:

DS1516MP000

### UPC Number:

70891715996

### Status:

Active

### Description:

MaxGard Male Plug, 100 Amp, 4 Pole 5 Wire, 30Y 120/208V, 60Hz

### Features

Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").

Two optional pilot/control pins for contractors, load monitor circuits, shunt trip or any other communication functions you need.

Center ground contacts: make FIRST, break LAST  
Standard delayed action pull and turn withdrawal offers all plugs an XP rating (30-100 amps).

### Application

Convention centers and arenas

For use in applications where outdoor, severe or high abuse environments exist.

Convention centers and arenas

### General

Style	Load Breaking Male Plug
Material	Copper Free, Cast Aluminum, Epoxy Powder-Coated Housing
Material_1	Standard Neoprene O-ring interior components
Material_2	Pin and sleeves are made from CDA 360 and Marine-grade CDA 485 brass (200a nd 400 amp lines are silver-plated as well).
Frequency	60 Hz
Amperage	100 Amp
Pole/Wire	4P/5W
System	Heavy Industrial & Marine

### Dimension Information

Overall Dimensions	Available on Website
--------------------	----------------------

### Specifications

Voltage	3 PhaseY 120/208 Volts AC
Engineering Specifications	Available on Website

### Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	5.2 lbs. Each

### Application Support

Overview	Available on Website
Russellstoll Application Guide	Available on Website



**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)