



Representative

**Catalog Number:** DS2301FRA0K  
**Product ID:** 7TAA057030R0478  
**UPC Number:** 70891731135  
**Status:** A

MaxGard Female Receptacle with Angle Adapter and Control Contacts, 200 Amp, 3 Pole 4 Wire, 220/380V, 50Hz

### North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	Electrical hook-up of mobile medical imaging (MMI trailers).
Number Of Poles	3
Number Of Wires	4
Amperage Rating	200 Amp
Voltage Rating	380V
Material	Cast Aluminum

### European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	200A
Number of poles	3

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	15.38x11x11
Weight Uom	8.6 lbs. Each

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)