Thomas&Betts

Russellstoll

MaxGard Interconnection Systems

T&B Catalog Number: DS2504FP000

UPC Number: 70891717820

Status: Active

Description:

MaxGard Female Connector, 200 Amp, 4 Pole 5 Wire, 30Y 277/480V, 60Hz

Features

	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
	Two optional pilot/control pins for contractors, load monitor circuits, shunt trip or any other communication functions you need.
	Center ground contacts: make FIRST, break LAST
	All receptacles and connectors have a gated hotating disk on the face of the interior, engaged on insertion.

Application

	Electrical hook-up of mobile medical imging (MMI trailers).
	For use in applications where outdoor, severe or high abuse environments exist.
	Electrical hook-up of mobile medical imaging (MMI trailers).

General

Style	Load Breaking Female Connector
Material	Copper Free, Cast Aluminum, Epoxy Powder-Coated Housing
Material_1	Standard Neoprene O-ring interior components
Frequency	60 Hz
Amperage	200 Amp
Pole/Wire	4P/5W
System	Heavy Industrial & Marine

Dimension Information

Overall Dimensions	Available on Website

Specifications

Voltage	3 PhaseY 277/480 Volts AC
Engineering Specifications	Available on Website

Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	16.4 lbs. Each

Application Support

Overview	Available on Website
Russellstoll Application Guide	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com