



Representative

Catalog Number: DS2504FRABK
Product ID: 7TAA057030R0555
UPC Number: 70891729850
Status: A

MaxGard Female Receptacle with Angle Adapter, Junction Box and Control Contacts, 200 Amp, 4 Pole 5 Wire, 30Y 277/480V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	Electrical hook-up of mobile medical imaging (MMI trailers).
Number Of Poles	4
Number Of Wires	5
Amperage Rating	200 Amp
Voltage Rating	277V
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	200A
Number of poles	4

Packaging

Outer Quantity	1
Outer Dimensions (inches)	15.62x15.25x8.31
Weight Uom	28 lbs. Each

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com