



Representative

Catalog Number: DS2504MP000/DF2029
Product ID: 7TAA057030R0558
UPC Number: 70891730996
Status: A

MaxGuard Male Plug, 200 Amp, 4 Pole 5 Wire, 3 Phase Y 277/480V, 60Hz, with 1.813 Inch Bushing

North American Specifications (UNSPSC)

| | |
|------------------|--|
| UNSPSC | 39121404 Electrical sleeves |
| IGCC | 4528 Electrical sleeves |
| Brand Name | Russellstoll |
| Type | MaxGuard Interconnection Systems |
| Special Features | Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight"). |
| Application | Electrical hook-up of mobile medical imaging (MMI trailers). |
| Number Of Poles | 4 |
| Number Of Wires | 5 |
| Amperage Rating | 200 Amp |
| Voltage Rating | 277V |
| Material | Cast Aluminum |

European Specifications (ETIM)

| | |
|-------------------|--|
| ETIM | EC001322 Round socket/plug for high currents |
| Amperage | 200A |
| Construction type | Plug |
| Number of poles | 4 |

Packaging

| | |
|---------------------------|-----------------|
| Outer Quantity | 1 |
| Outer Dimensions (inches) | 15x8x8 |
| Weight Uom | 11.76 lbs. Each |

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com