



Representative

Catalog Number: DS2504MP000/DF2034
Product ID: 7TAA057800R0002
UPC Number: 70891740329
EAN Number: 05415022010282
Status: Active

MaxGuard Male Plug, 200 Amp, 4 Pole 5 Wire, 3 Phase Y 277/480V, 60Hz, with 2.125 Inch Bushing

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGuard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	Electrical hook-up of mobile medical imaging (MMI trailers).
Number Of Poles	4
Number Of Wires	5
Amperage Rating	200 Amp
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	200A
Construction type	Plug
Number of poles	4

Packaging

Outer Quantity	1
Outer Dimensions (inches)	15x8x8
Weight Uom	10.9 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com