



Representative

**Catalog Number:** DS3107MP00K  
**Product ID:** 7TAA057030R0605  
**UPC Number:** 70891730862  
**Status:** A

MaxGard Male Plug with Control Contacts, 30 Amp, 2 Pole 3 Wire, 125V, 60Hz

### North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	Russellstoll Hazardous Locations
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	For use in "People Movers" which require air conditioning and heater unit power when docked at end of line locations for maintenance and overhaul, ex: Dulles Airport.
Standard	UL E68085
Number Of Poles	2
Number Of Wires	3
Amperage Rating	30 Amp
Voltage Rating	125V
Material	Cast Aluminum

### European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Construction type	Plug
Number of poles	2

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	8.63x4.75x4.63
Weight Uom	3 lbs. Each

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
 www.tnb.com

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com